

USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS

4290 COLUMBIAN ROAD WAMEGO, KS

ORIGINAL CONTRACT DOCUMENTS

Owner:

USD 320 SCHOOL DISTRICT
1008 8TH ST.
WAMEGO, KS 66547

ARCHITECT:

BBN ARCHITECTS, INC.
228 POYNTZ AVE.
MANHATTAN, KS 66502
TELEPHONE: (785) 776-4912

MEP ENGINEER:

ORAZEM & SCALORA ENGINEERING, P.A.
2312 ANDERSON AVE.
MANHATTAN, KS 66502

STRUCTURAL ENGINEER:

DUDLEY WILLIAMS AND ASSOCIATES, P.A.
230 S LAURA SUITE #200
WICHITA, KS 67211

CIVIL ENGINEER:

SMH CONSULTANTS
2017 VANESTA PL.
MANHATTAN, KS 66503

PROJECT DESCRIPTION:


NEW LOCKER ROOM, CONCESSIONS, AND MEETING ROOM FOR THE SPORTS COMPLEX TO REPLACE THE EXISTING LOCKER ROOM.

INDEX TO DRAWINGS:

T101	COVER SHEET
CF101	CODE REVIEW
CF102	CODE PLAN
C1	DEMOLITION DETAIL
C2	SITE PLAN
C3	GRADING PLAN
C4	HORIZONTAL & VERTICAL CONTROL PLAN
C5	JOINTING PLAN
C6	HANDRAIL DETAIL
C7	STORM F4P
C8	SEEG PLAN
C9	MISCELLANEOUS DETAILS
S101	FOUNDATION PLAN
S102	ROOF FRAMING PLAN
S201	GENERAL STRUCTURAL NOTES
S202	NOTES, SCHEDULES, AND DETAILS
S203	SCHEDULES AND DETAILS
S301	FOUNDATION SECTIONS AND DETAILS
S302	FOUNDATION SECTIONS AND DETAILS
S401	FRAMING SECTIONS AND DETAILS
S402	FRAMING SECTIONS AND DETAILS
A001	GENERAL INFORMATION
A002	DEMOLITION PLAN
A003	WALL TYPES
A101	SITE PLAN
A102	FLOOR PLAN
A103	REFLECTED CEILING PLAN
A104	ROOF PLAN
A201	EXTERIOR ELEVATIONS
A202	INTERIOR ELEVATIONS
A301	BUILDING SECTIONS
A302	WALL SECTIONS
A303	WALL SECTIONS
A301	DETAILS
A602	DOOR SCHEDULE AND DETAILS
A601	ROOM FINISH SCHEDULE
A701	DOOR AND WINDOW DETAIL
A702	WINDOW DETAILS
A703	SITE DETAILS
A901	FURNISHING PLAN
ME101	MEP SITE PLAN
M101	MECHANICAL PLAN
F101	PLUMBING PLANS
F201	PLUMBING DETAILS
F202	PLUMBING DETAILS
F203	PLUMBING DETAILS
E101	ELECTRICAL PLANS
E201	ELECTRICAL DETAILS

GENERAL NOTES

1. GENERAL NOTES APPLY TO ALL ARCHITECTURAL DRAWINGS & DETAILS.
2. ALL WORK SHALL CONFORM WITH APPLICABLE BUILDING CODES, REGULATIONS, AND ORDINANCES. CONTRACTOR SHALL OBTAIN ALL REQUIRED PERMITS.
3. DESIGN DOCUMENTS HAVE BEEN PREPARED DESCRIBING GENERAL REQUIREMENTS FOR WORK AT THE EXISTING SITE. IDENTIFICATION OF EXISTING CONDITIONS, SHOWN ON THE PLANS, IS BASED ON A GENERAL REVIEW OF EXISTING CONDITIONS. THE CONTRACTOR SHALL VERIFY EXISTING CONDITIONS PRIOR TO PROCEEDING WITH CONSTRUCTION AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES.
4. THE CONTRACTOR SHALL VERIFY ALL LAYOUT DIMENSIONS AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO PROCEEDING WITH CONSTRUCTION.
5. CONTRACTOR SHALL COORDINATE THE WORK WITH THE INSTALLATION OF ALL EQUIPMENT/TRADES SHOWN ON THE PLANS.
6. CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR MEANS, METHODS, AND SEQUENCES OF CONSTRUCTION AND THE SAFETY OF ALL CONSTRUCTION PERSONNEL AND AUTHORIZED VISITORS TO THE PROJECT SITE.
7. WHERE DISCREPANCIES EXIST IN THE DOCUMENTS THE MOST STRINGENT SHALL APPLY.
8. PATCH, FINISH AND REPAINT ANY WALLS, FLOOR AND CEILINGS DAMAGED OR REMOVED WHILE INSTALLATION OF NEW WATER PIPING.
9. REMOVE AND DISPOSE OF ALL EXISTING FIXTURES, CASEWORK, PARTITIONS, CEILINGS, INSULATION, AND ALL OTHER FINISHES REQUIRED PRIOR TO RENOVATION WORK.



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.



Project Number: **16036**

Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
COVER SHEET

Sheet: **T101**

Of:

GENERAL INFORMATION

LOCATION: **USD 320 SPORTS COMPLEX
LOCKER AND CONCESSIONS
4290 COLUMBIAN ROAD
WAMEGO, KS**

OWNER INFORMATION: **USD 320 SCHOOL
DISTRICT
1008 8TH
ST. WAMEGO, KS
66547**

RESPONDING FIRE
DEPARTMENT: **WAMEGO FIRE DEPARTMENT
428 LINCOLN AVE.
WAMEGO, KS 66547
(785) 456-9553**

ARCHITECT: **BBN ARCHITECTS, INC.
228 POYNTZ AVE.
MANHATTAN, KS 66502
TELEPHONE: (785) 776-4912**

PROJECT CONSTRUCTION
PURPOSE FOR SUBMITTAL: **NEW CONSTRUCTION**

AUTHORITIES HAVING
JURISDICTION: **WAMEGO FIRE DEPARTMENT
428 LINCOLN AVE.
WAMEGO, KS 66547
(785) 456-9553**

PROJECT DESCRIPTION

NEW CONSTRUCTION FOR LOCKER ROOM, MEETING, CONCESSIONS AND PUBLIC RESTROOM FACILITIES. REPLACING EXISTING LOCKER ROOM BUILDING.

APPLICABLE CODES

2012 INTERNATIONAL BUILDING CODE	2011 NATIONAL ELECTRIC CODE	2010 NFPA 10
2012 INTERNATIONAL MECHANICAL CODE	2012 INTERNATIONAL FIRE CODE	2010 NFPA 13
2012 INTERNATIONAL PLUMBING CODE	KANSAS FIRE PREVENTION CODE	2010 NFPA 14
2012 INTERNATIONAL FUEL GAS CODE	2010 ADA STANDARD FOR ACCESSIBLE DESIGN	2010 NFPA 25
2012 INTERNATIONAL ENERGY CODE	2010 ASHRAE 90.1	2010 NFPA 72
		2003 NFPA 92B

BUILDING HEIGHTS AND AREAS

CONSTRUCTION CLASSIFICATION

BASIC ALLOWABLE AREA AND HEIGHT:

CONSTRUCTION TYPE: **V-B**

ALLOWABLE AREA: 9,500 S.F.

ALLOWABLE HEIGHT: 40 FEET

ACTUAL AREA: 7,382 S.F.

ACTUAL HEIGHT: 17'-10"

STRUCTURAL FRAME INCLUDING COLUMNS, GIRDERS & TRUSSES:	0-HR
BEARING EXTERIOR WALLS:	0-HR
BEARING INTERIOR WALLS:	0-HR
NONBEARING EXTERIOR WALLS (<30' FROM ADJACENT BUILDING OR PROPERTY LINE):	0-HR
NONBEARING INTERIOR WALLS:	0-HR
FLOOR CONSTRUCTION INCLUDING SUPPORTING BEAMS & JOISTS:	0-HR
ROOF CONSTRUCTION INCLUDING SUPPORTING BEAMS & JOISTS:	0-HR

OCCUPANCY CLASSIFICATION

EXIT WIDTH FACTORS

GROUP E (EDUCATIONAL)

**STAIRS: .30" / PERSON
DOORS, LEVEL SURFACES, RAMPS: 20" / PERSON**

NON-CONFORMING ITEMS


PASSIVE LIFE SAFETY SYSTEMS

CORRIDOR RATINGS: 1-HOUR
EXIT STAIR ENCLOSURES: 1-HR WITH 45-MINUTE DOORS
SHAFTS: 1-HR WITH 45-MINUTE DOORS
OCCUPANCY SEPERATIONS: NONE

ACTIVE LIFE SAFETY SYSTEMS


FIRE ALARM: FACP: EMERGENCY VOICE ALARM COMMUNICATION: REMOTE ANNUNCIATOR PANEL: SMOKE DETECTION: EXIT SIGNS: EMERGENCY LIGHTS: BACKUP POWER: STANDPIPES: AUTOMATIC SPRINKLERS: FIRE EXTINGUISHERS: FIRE PUMP: PRESSURIZED EXIT STAIRS: PRESSURIZED ELEVATORS: MANUAL FULL STATIONS:	REQUIRED/PROVIDED REQUIRED/PROVIDED REQUIRED/PROVIDED REQUIRED/PROVIDED NOT REQUIRED/NOT PROVIDED REQUIRED/PROVIDED REQUIRED/PROVIDED NOT REQUIRED/NOT PROVIDED NOT REQUIRED/NOT PROVIDED NOT REQUIRED/NOT PROVIDED REQUIRED/PROVIDED NOT REQUIRED/NOT PROVIDED NOT REQUIRED/ NOT PROVIDED NOT REQUIRED/ NOT PROVIDED REQUIRED/PROVIDED	PER IBC SECTIONS 907.2 PER IBC SECTION 907.5.2.2 BATTERY BACKUP BATTERY BACKUP MULTI-PURPOSE CLASS 4A-80B:C 10 LBS
---	---	--

SYMBOL	DESCRIPTION	PROTECTIVE ELEMENTS/NOTES
	EXIT - EXTERIOR	
	EXIT - INTERIOR	EXITS FROM FLOOR OR ASSEMBLY OCCUPANTS OVER 50 OCCUPANTS
	FIRE EXTINGUISHER	
	FIRE EXTINGUISHER SPACING	75' RADIUS SHOWN ON FLOOR PLANS
	NON PROTECTED EXIT PATH	[NONE] OR [NONE-PER EXCEPTION FO FULLY SPRINKLERED A, B, E, F, M, S, U OCCUPANCY] OR [1-2 OCCUPANCY SMOKE PARTITION WALLS (NO FIRE RESISTIVE WALL RATING. DOORS LIMIT TRANSFER OF SMOKE AND SHALL HAVE POSITIVE LATCHING.)]
	1 HOUR EXIT PASSAGEWAY	1-HOUR FIRE BARRIER WALL CONSTRUCTION. NO OPENINGS OTHER THAN REQUIRED EXIT DOORS. 1-HOUR DOOR ASSEMBLY.
	2 HOUR EXIT PASSAGEWAY	2-HOUR FIRE BARRIER WALL CONSTRUCTION. NO OPENINGS OTHER THAN REQUIRED EXIT DOORS. 1 1/2-HOUR DOOR ASSEMBLY.
	1 HOUR EXIT STAIR ENCLOSURE (<3 STORIES OR LESS)	1-HOUR FIRE BARRIER WALL CONSTRUCTION. NO OPENINGS OTHER THAN REQUIRED EXIT DOORS. 1-HOUR DOOR ASSEMBLY.
	2 HOUR EXIT STAIR ENCLOSURE (<4 STORIES OR LESS)	2-HOUR FIRE BARRIER WALL CONSTRUCTION. NO OPENINGS OTHER THAN REQUIRED EXIT DOORS. 1 1/2-HOUR DOOR ASSEMBLY.
	1 HOUR FIRE BARRIER (OCC & INCIDENTAL USE)	1-HOUR FIRE BARRIER WALL CONSTRUCTION. 3/4-HOUR DOOR ASSEMBLY. FIRE DAMPERS.
	2 HOUR FIRE BARRIER (OCC)	2-HOUR FIRE BARRIER WALL CONSTRUCTION. 1 1/2-HOUR DOOR ASSEMBLY. FIRE DAMPERS.
	1 HOUR SHAFT (3 STORIES OR LESS)	1-HOUR FIRE BARRIER WALL CONSTRUCTION. 1-HOUR DOOR ASSEMBLY. FIRE/SMOKE DAMPERS
	1 HOUR SHAFT (3 STORIES OR LESS)	1-HOUR FIRE BARRIER WALL CONSTRUCTION. 1-HOUR DOOR ASSEMBLY. FIRE/SMOKE DAMPERS
	SPRINKLERED INCIDENTAL USE AREAS	WALL CONSTRUCTION TO RESIST THE PASSAGE OF SMOKE FROM THE FLOOR TO FIRE-RATED FLOOR/CEILING ASSEMBLY. SELF-OR AUTOMATIC-CLOSING DOORS WITH NO AIR TRANSFER GRILLES.
	ACCUMULATED EXIT WIDTH AT REQUIRED EXIT (CLEAR WIDTH)	OCCUPANTS / REQUIRED WIDTH PROVIDED WIDTH
	PUBLIC FIRE HYDRANT	DISTANCE FROM BUILDING SHOWN ON SITE PLAN
	CONF./A4 65	ROOM DESIGNATION ROOM TYPE / OCCUPANCY TPE MAXIMUM ALLOWABLE OCCUPANTS
	80 140	ACCUMULATED OCCUPANT LOADS FOR COMPLEX PATHS
	NON-WORK AREAS	EXISTING CONSTRUCTION NOT INCLUDED IN THE RENOVATION PROJECT. ALL OTHER AREAS ARE EXISTING CONSTRUCTION TO BE REMODELED
	SPRINKLER/STANDPIPE RISER	
	FIRE DEPARTMENT CONNECTION	
	FACP	FIRE ALARM CONTROL PANEL
	ANN	FIRE ALARM ANNUNCIATOR PANEL
	FIRE DEPARTMENT KNOX BOX	
	EXIT SIGN	



BBN ARCHITECTS INC
228 POYNTZ AVENUE,
MANHATTAN, KANSAS 66502
PH: 785-776-4912
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.



Project Number: **16036**

Date: **7/7/17**

Project Name:


**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:

CODE REVIEW

Sheet:
CF101



BBN ARCHITECTS INC
 228 POYNTZ AVENUE,
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.



Project Number: 16036

Date: 7/7/17

Project Name:


**USD 320 SPORTS
 COMPLEX LOCKER
 AND CONCESSIONS**

Project Address:
 4290 COLUMBIAN ROAD
 WAMEGO, KS














Sheet Title:

CODE PLAN

Sheet:
CF102




LEGEND




-  EXISTING CONCRETE TO BE REMOVED
-  EXISTING CONCRETE TO REMAIN
-  EXISTING ASPHALT TO BE REMOVED
-  EXISTING GRAVEL TO BE REMOVED & STOCKPILED
-  EXISTING BUILDING TO BE REMOVED
-  PROPOSED BUILDING
-  WATER STRUCTURES
-  TELEPHONE STRUCTURES
-  SANITARY SEWER SERVICE LINE
-  WATER SERVICE LINE
-  GAS LINE
-  FIBER OPTIC CABLE
-  UNDERGROUND ELECTRIC

NOTES:

- CONTRACTOR TO COORDINATE ALL DEMOLITION AND PHASING OF DEMOLITION WITH ARCHITECT.
- ALL CONSTRUCTION WORK AND UTILITY WORK OUTSIDE OF THE PROPERTY BOUNDARIES SHALL BE PERFORMED IN COOPERATION WITH AND IN ACCORDANCE WITH REGULATIONS OF THE AUTHORITIES CONCERNED.
- FOR CONSTRUCTION OF NEW SIDEWALK, PARTIAL PANEL REMOVAL OF EXISTING SIDEWALK WILL NOT BE ALLOWED. IF A PARTIAL PANEL IS REMOVED THEN ENTIRE PANEL SHALL BE REMOVED AND REPLACED AS NEEDED.
- ALL TREES ARE TO REMAIN UNLESS OTHERWISE NOTED.
- TREES AND SHRUBS WHICH ARE IN DIRECT CONFLICT WITH PROPOSED NEW CONSTRUCTION SHALL BE REMOVED AND DISPOSED OF BY THE CONTRACTOR WITH THE ENGINEER'S APPROVAL. TREES AND SHRUBS WHICH ARE NOT IN CONFLICT WITH PROPOSED NEW CONSTRUCTION AND NOT SHOWN TO BE REMOVED SHALL BE SAVED AND PROTECTED FROM DAMAGE.
- TREE PROTECTION MEASURES SHALL BE IMPLEMENTED FOR ANY TREE WHICH WILL HAVE CONSTRUCTION ACTIVITY LOCATED WITHIN 5 FEET OF THE DRIP LINE.
- MINIMIZE DISTURBANCE OF ROOTS WITHIN DRIP LINES OF TREES WHERE CONSTRUCTION ACTIVITY IS PLANNED.
- INSTALL TEMPORARY TREE PROTECTION MEASURES PRIOR TO COMMENCING ANY REMOVAL OR SITE DEMOLITION WORK. INSPECT TREE PROTECTION FENCE DAILY, AND MAINTAIN THROUGHOUT THE DURATION OF CONSTRUCTION. REMOVE FENCE WHEN CONSTRUCTION IS COMPLETE.
- DO NOT STORE MATERIALS, DEBRIS, OR SALVAGED OR EXCAVATED MATERIALS INSIDE THE TREE PROTECTION ZONE. DO NOT PARK VEHICLES OR EQUIPMENT INSIDE THE TREE PROTECTION ZONE.
- ALL DEMOLITION DEBRIS SHALL BE REMOVED FROM THE SITE. NO ON-SITE BURYING OF DEBRIS WILL BE ALLOWED.
- ALL HAUL SITES SELECTED FOR COLLECTION OF DEBRIS SHALL BE APPROVED BY THE OWNER/ENGINEER.
- IN LOCATIONS WHERE PROPOSED IMPROVEMENTS ARE NOT LOCATED, REMOVE STUMPS, ROOTS, AND OTHER DEBRIS PROTRUDING THROUGH GROUND SURFACE TO A DEPTH OF 24 INCHES BELOW FINISH SUBGRADE ELEVATION. IN ALL OTHER LOCATIONS COMPLETE REMOVAL IS REQUIRED.
- EXISTING SEPTIC TANKS SHALL BE PUMPED EMPTY, TOP CRUSHED IN, AND BACKFILLED WITH SAND. ALL OTHER LINES MAY BE CAPPED. COORDINATE SEPTIC TANK ABANDONMENT WITH: SCOTT SCHWINN, R.S. COUNTY SANITARIAN, 612 E. CAMPBELL ST. WESTMORELAND, KS 66549 785-457-3397



TREE PROTECTION DETAIL
NOT TO SCALE





BBN

BBN ARCHITECTS INC
228 POYNITZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

SMH CONSULTANTS
2017 Vanesta Place, Suite 110
Manhattan, KS 66503
P (785)776-0541 • F (785)776-9760



REV	DESCRIPTION	DATE

Project Number: **16036**

Date: **7/7/17**


Project Name:
USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS

Project Address:
4290 COLUMBIAN ROAD WAMEGO, KS

Sheet Title:
DEMOLITION PLAN

Sheet:
C1

Of:



CONCRETE RETAINING WALL A-A DETAIL
NOT TO SCALE

HORIZONTAL CONTROL

HCP #5:	N:323148.454	E:1786693.193	ELEV:1103.28
HCP #6:	N:323053.717	E:1787026.513	ELEV:1093.44
HCP #7:	N:322421.159	E:1787060.645	ELEV:1093.33
HCP #8:	N:322631.502	E:1786831.935	ELEV:1095.92

NOTE: HCP'S 6, 7, & 8 ARE NOT VISIBLE ON THIS SHEET.

NOTES:

ALL SOIL BROUGHT TO THE SITE AND IN SITU SHALL BE COMPACTED BY ROLLING WITH A SHEEPSFOOT ROLLER OR BY MECHANICAL TAMPING. THE SHEEPSFOOT ROLLER, WHEN FULLY LOADED, SHALL HAVE A LOAD ON EACH TAMPER FOOT NO LESS THAN 200 POUNDS PER SQUARE INCH OF CROSS-SECTIONAL AREA. ENOUGH MOISTURE SHALL BE PRESENT IN THE SOIL TO OBTAIN A DENSITY EQUAL TO OR GREATER THAN 95% OF MAXIMUM DENSITY AS DETERMINED BY THE STANDARD PROCTOR DENSITY TEST BEFORE PLACING THE NEXT LIFT. EACH LIFT SHALL CONSIST OF 8-INCH LOOSE LIFTS OR LESS PRIOR TO COMPACTION. FILL MATERIAL SHALL BE APPROVED BY A LICENSED ENGINEER.



THE CROSS SLOPES OF ALL SIDEWALKS SHALL BE 2% OR LESS.

ALL GRADE AGAINST THE BUILDING SHALL BE 3" BELOW FINISH FLOOR UNLESS OTHERWISE SPECIFIED.

ALL STRIPPED TOPSOIL SHALL BE STOCKPILED FOR RE-USE.

ALL GRAVEL WITHIN THE GRADING LIMITS SHALL BE STRIPPED AND STOCKPILED. STRIPPED GRAVEL SHALL BE COMBINED WITH AB-3 AND RE-APPLIED WITHIN GRAVEL PARKING AREA.

DUE TO EXISTING LOCKER ROOM REMAINING IN PLACE AND OPERATIONAL AS NEW BUILDING IS CONSTRUCTED, CONTRACTOR TO ENSURE THAT AREA BETWEEN EXISTING AND PROPOSED BUILDINGS WILL DRAIN UNTIL EXISTING BUILDING IS DEMOLISHED AND REMAINING CONSTRUCTION IN PLAZA AREA IS COMPLETED.





BBN

BBN ARCHITECTS INC
228 POYNITZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

SMH
CONSULTANTS

2017 Vanesta Place, Suite 110
Manhattan, KS 66503
P (785)776-0541 • F (785)776-9760



REV	DESCRIPTION	DATE

Project Number: **16036**

Date: **7/7/17**


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
**GRADING
PLAN**

Sheet:
C3

Of:





BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

SMH CONSULTANTS

2017 Vanesta Place, Suite 110
Manhattan, KS 66503
P (785)776-0541 • F (785)776-9760



REV	DESCRIPTION	DATE
-----	-------------	------

Project Number: **16036**

Date: **7/7/17**


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**



Sheet Title:
JOINT PLAN

Sheet:
C5


Of:




ROOF DRAIN PROFILE




STORM DRAIN PROFILE




NYLOPLAST 30" DRAIN BASIN: 2830AG
NOT TO SCALE



3130 VERONA AVE
BUFORD, GA 30518
PHN (770) 932-2443
FAX (770) 932-2490
www.nyloplast-us.com



1. GRATES/SOLID COVER SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
2. FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
3. DRAIN BASIN TO BE CUSTOM MANUFACTURED ACCORDING TO PLAN DETAILS. RISERS ARE NEEDED FOR BASINS OVER 84" DUE TO SHIPPING RESTRICTIONS. SEE DRAWING NO. 7001-110-065
4. DRAINAGE CONNECTION STUB JOINT TIGHTNESS SHALL CONFORM TO ASTM D3212 FOR CORRUGATED HDPE (ADS N-12/HANCOR DUAL WALL) & PVC SEWER (4" - 24")
5. ADAPTERS CAN BE MOUNTED ON ANY ANGLE 0° TO 360°. TO DETERMINE MINIMUM ANGLE BETWEEN ADAPTERS SEE DRAWING NO. 7001-110-013.




BBN

BBN ARCHITECTS INC
228 POYNITZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

SMH CONSULTANTS

2017 Vanesta Place, Suite 110
Manhattan, KS 66503
P (785) 776-0541 • F (785) 776-9760



REV	DESCRIPTION	DATE

Project Number: **16036**

Date: **7/7/17**


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
STORM P&P

Sheet:
C7

LEGEND



NOTES:
 CONTRACTOR TO COMPLY WITH CITY OF WAMEGO STORM WATER MANAGEMENT REQUIREMENTS AS WELL AS THE PROVIDED STORM WATER POLLUTION PREVENTION PLAN (SWPPP) AND SOIL EROSION AND SEDIMENT CONTROL PLAN.


TEMPORARY SEEDING SHALL INCLUDE ALL DISTURBED SOIL UNLESS OTHERWISE NOTED AS PERMANENT SEEDING.

ALL INLETS SHALL BE ADEQUATELY PROTECTED DOWNSTREAM FROM CONSTRUCTION AREA

EXISTING VEGETATION SHALL BE MAINTAINED IN ALL AREAS AS STORM WATER POLLUTION PREVENTION WITH THE EXCEPTION OF THOSE AREAS NOTED TO BE DISTURBED ON THIS PLAN SHEET.

CONTRACTOR SHALL DESIGNATE TRUCK WASHOUT AREA.

CONSTRUCTION ENTRANCE IS INDICATED ON CENTRAL KITCHEN SESC PLAN.




NOTES FOR AREA INLET PROTECTION:



- SURROUND WIRE WRAPPED ROCK WATTLE, FILLED WITH 1 1/2" DIA. CLEAN ROCK, AROUND AREA INLET AS SHOWN.
- INSURE EACH NEW WRAP DOES NOT BEGIN AND END IN THE SAME PLACE AS THE PREVIOUS.
- USE A MINIMUM OF THREE (3) WATTLES AROUND EACH INLET, STACKED AS SHOWN.

* WHERE CLEAN ROCK IS NOT AVAILABLE, OTHER WADDLE MATERIAL MAY BE SUBSTITUTED. SUITABLE MATERIAL WILL NOT DETERIORATE OR DECOMPOSE DUE TO AGE OR WEATHER.

AREA INLET PROTECTION



SILT FENCE BARRIER





BBN

BBN ARCHITECTS INC
 228 POYNIZ AVENUE
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912 - FAX: 785-776-0944
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

SMH CONSULTANTS

2017 Vanesta Place, Suite 110
 Manhattan, KS 66503
 P (785)776-0541 • F (785)776-9760



REV	DESCRIPTION	DATE

Project Number: **16036**

Date: **7/7/17**


Project Name:
USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS

Project Address:
4290 COLUMBIAN ROAD WAMEGO, KS


Sheet Title:
SESC PLAN

Sheet:
C8


Of:




CONCRETE WHEEL STOP PLAN DETAIL
NOT TO SCALE




CONCRETE WHEEL STOP ELEVATION DETAIL
NOT TO SCALE




CONCRETE WHEEL STOP SECTION DETAIL
NOT TO SCALE



GRADE ADJACENT TO BUILDING DETAIL
NOT TO SCALE



SIDEWALK ADJACENT TO BUILDING DETAIL
NOT TO SCALE



NOTE:

THE CONTRACTOR SHALL PROVIDE AN ACCESSIBLE PARKING SIGN FOR EACH ACCESSIBLE PARKING SPACE INDICATED.


THE CONTRACTOR SHALL PROVIDE A VAN ACCESSIBLE SIGN AT ACCESSIBLE PARKING SPACES AS INDICATED.

THE ACCESSIBLE PARKING SIGNS PROVIDED SHALL CONFORM TO TYPE "R7-8" IN ACCORDANCE WITH THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES".


ACCESSIBLE STALL SIGN DETAIL
NOT TO SCALE

PART #	PIPE SIZE	A	B	C	JOINT
**0670AN	6X4 in (150x100mm)	11.4 in (291mm)	6.2 in (157mm)	5.3 in (133mm)	*
**0870AN	8x4 in (200x100mm)	12.0 in (304mm)	6.7 in (171mm)	5.3 in (135mm)	*
**0871AN	8x6 in (200x150mm)	12.9 in (328mm)	6.7 in (171mm)	6.2 in (157mm)	*
**1070AN	10x4 in (250x100mm)	12.8 in (325mm)	7.6 in (192mm)	5.3 in (133mm)	*
**1071AN	10x6 in (250x150mm)	13.8 in (349mm)	7.6 in (192mm)	6.2 in (157mm)	*
**1072AN	10x8 in (250x200mm)	14.3 in (363mm)	7.6 in (192mm)	6.7 in (171mm)	*
1270AN	12x4 in (300x100mm)	11.0 in (280mm)	5.8 in (146mm)	5.3 in (133mm)	*
1270AN6SB	12x4 in (300x100mm)	8.9 in (226mm)	6.5 in (165mm)	2.4 in (60mm)	WT
1271AN	12x6 in (300x150mm)	12.0 in (304mm)	5.8 in (146mm)	6.2 in (157mm)	*
1271AN6SB	12x6 in (300x150mm)	10.0 in (254mm)	6.5 in (165mm)	3.5 in (89mm)	WT
1272AN	12x8 in (300x200mm)	12.5 in (317mm)	5.8 in (146mm)	6.7 in (171mm)	*
1272AN6SB	12x8 in (300x200mm)	10.8 in (273mm)	6.5 in (165mm)	4.3 in (108mm)	WT
1273AN	12x10 in (300x250mm)	13.3 in (338mm)	5.8 in (146mm)	7.6 in (192mm)	*
1273AN6SB	12x10 in (300x250mm)	11.8 in (298mm)	6.5 in (165mm)	5.3 in (133mm)	WT

* = PLAIN END
WT = WATER TIGHT
** = LIMITED AVAILABILITY. PLEASE SEE INJECTION MOLDED FITTING SECTION FOR OTHER AVAILABLE FITTINGS
NOTE: ALL FITTINGS DIMENSIONS ARE FOR REFERENCE ONLY.






DUAL WALL FABRICATED REDUCERS
6"X4" - 12"X10" DIAMETER




PART #	PIPE SIZE	A	B(MAX)	H	L	W
1270AN	12 in (300 mm)	6.5 in (165mm)	10.0 in (254mm)	6.5 in (165mm)	25.0 in (635mm)	29.0 in (737mm)
1510NP	15 in (375mm)	6.5 in (165mm)	10.0 in (254mm)	6.5 in (165mm)	25.0 in (635mm)	29.0 in (737mm)
1810NP	18 in (450mm)	7.5 in (191mm)	15.0 in (381mm)	6.5 in (165mm)	32.0 in (813mm)	35.0 in (889mm)
2410NP	24 in (600mm)	7.5 in (191mm)	18.0 in (457mm)	6.5 in (165mm)	36.0 in (914mm)	45.0 in (1143mm)
3015NP	30 in (750mm)	7.5 in (191mm)	12.0 in (305mm)	8.6 in (218mm)	58.0 in (1473mm)	63.0 in (1600mm)
3615NP	36 in (900mm)	7.5 in (191mm)	25.0 in (635mm)	8.6 in (218mm)	58.0 in (1473mm)	63.0 in (1600mm)

NOTE: ALL DIMENSIONS ARE NOMINAL


FLARED END SECTIONS




CONTRACTION JOINT DETAIL - 6" CONCRETE
NOT TO SCALE



CONSTRUCTION JOINT DETAIL
NOT TO SCALE



JOINT SEALER RESERVOIR
NOT TO SCALE



BBN

BBN ARCHITECTS INC
238 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

SMH
CONSULTANTS

2017 Vanesta Place, Suite 110
Manhattan, KS 66503
P (785)776-0541 • F (785)776-9760



REV	DESCRIPTION	DATE

Project Number: **16036**


Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**


Sheet Title:
MISC. DETAILS

Sheet:
C9



4" Concrete Slab On Grade
Reinforce W/ 6x6-#2, 1x#2, 1 #WR
Elevation Top of Slab At 100-0

4" Concrete Slab On Grade
Reinforce W/ 6x6-#2, 1x#2, 1 #WR
Elevation Top of Slab At 100-0



FOUNDATION PLAN

1/8" = 1'-0"

FOUNDATION PLAN MARKS:


- TX Trench Footing Mark, See Trench Footing Schedule on Sheet S202
- WX Foundation Wall Mark, See Foundation Wall Schedule on Sheet S202
- TOW Top of Concrete Wall Elevation
- S# Steel Column Mark, See Schedule on Sheet S203
- C# Steel Column Mark, See Schedule on Sheet S203
- C# Concrete Column and Footing Mark, See Schedule on Sheet S202

FOUNDATION PLAN GENERAL NOTES:

1. See General Structural Notes on Sheet S201 and specifications for additional notes and information.
2. Perimeter Foundation Plan dimensions on the exterior of the building are to the exterior face of concrete masonry wall, concrete foundation wall, masonry veneer, centerline of steel column, or edge of slab on grade, unless noted otherwise. Dimensions on the interior of the building are to face of concrete masonry wall, unless noted otherwise.
3. See Detail 1-S301 for Typical Corner Bar Detail.
4. See Detail 2-S301 for Typical Slab on Grade Joint Details. Locate interior slab on grade joints in accordance with the General Structural Notes on Sheet S201. See Architectural and Civil Drawings for exterior concrete slab on grade details.
5. Thicken trench footings per Detail 3-S301 at all locations where subgrade plumbing/electrical lines occur less than 2'-0" below scheduled bottom of footing elevation. Verify locations required with Civil Drawings, Architectural Drawings, Mechanical Drawings, Electrical Drawings, and field conditions.
6. See Detail 4-S301 for typical masonry expansion and control joint details. See Details 5-S301 for typical masonry jamb details at Intel Bearing. See Detail 10-S301 for typical masonry wall reinforcing and grouting details.
7. See Sheet S301 for typical foundation details.
8. See the Architectural and Civil Drawings for additional exterior slab and paving details. See the Mechanical and Electrical Drawings for equipment pad details, unless indicated otherwise on Structural Drawings.

REFERENCED PLAN NOTES:

- ① Slope floor slab to floor drains. See Architectural drawings for floor drain location and floor slab elevations at drains. Maintain the defined floor slab thickness at all areas with a sloped top of slab elevation.




BBN

BBN ARCHITECTS INC
228 FOYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

DWA Dudley Williams and Associates, PA
2301 West 20th Street, Suite 200 • Wichita, KS 67215-1514
316-263-7910 • www.dwa.com
17-045.01 S101 in 17-045(17-045.01)S-1X 7/7/2017 (40) (194)





REV	DESCRIPTION	DATE

Project Number: **16036**
Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**
Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
**FOUNDATION
PLAN**

Sheet:
S101
Of:



ROOF FRAMING PLAN

1/8" = 1'-0"

ROOF FRAMING PLAN MARKS:


- S#** Steel Column Mark, See Steel Column Schedule on Sheet S203
- LX#** Lintel Mark, See Lintel Schedule on Sheet S203; See Architectural Drawings for size and location of door and window openings. See Architectural and Mechanical Drawings for size and location of mechanical openings.
- ###-##** Truss Bearing Elevation / Top of Wood Beam or Wood Plate Elevation
- SST** Simpson Strong-Tie
- PSL** Parallel Strand Lumber Framing Member, See General Structural Notes on Sheet S201
- BX#** Bearing Plate Mark, See Bearing Plate Schedule on Sheet S203
- **K** Beam Vertical Shear End Reaction in kips; 10K minimum if not noted.

ROOF FRAMING PLAN KEY NOTES:

- 1 Wood Panel Roof Sheathing Type I. See General Structural Notes on Sheet S201 for fastener requirements and additional information.
- 2 Pre-fabricated Wood Trusses at 24" o.c. See General Structural Notes on Sheet S201 and sections for design loading requirements and additional information. (Provide king post truss bearing where shown on sections.)
- 3 Pre-fabricated Wood Jack Trusses at 24" o.c. Truss fabricator to design truss to truss connection hardware. See General Structural Notes on Sheet S201 for design loading requirements and additional information.
- 4 2x6 Roof Framing at 24" o.c. See Architectural Drawings for soffit details, typical.
- 5 Pre-fabricated Wood Hip Girder Truss. Truss fabricator to design truss to truss connection hardware. See General Structural Notes on Sheet S201 for design loading requirements and additional information. Anchor hip girder truss to wall top plates or wood beam with SST-H2.5T anchor.
- 6 Pre-fabricated Wood Girder Truss. Truss fabricator to design truss to truss connection hardware. See General Structural Notes on Sheet S201 for design loading requirements and additional information. Anchor girder truss to exterior face of concrete masonry wall with SST-L6T girder truss tie down with Titan screw anchors. Determine SST-L6T tie down model based on the provided number of girder truss plies. Coordinate number of girder truss plies with wood truss supplier.
- 7 Anchor each girder truss to steel beam per Detail 18-S401.
- 8 5x4 1/2 PSL Roof Beam. See General Structural Notes on Sheet S201 for additional information. Frame beam into steel column with column cap per Details 5 or 6-S402.
- 9 2x6 Outriggers at 24" o.c. See Architectural Drawings for soffit details, typical.
- 10 Provide 3 bays of pre-fabricated blocking trusses between roof trusses at maximum 16'-0" o.c. see General Structural Notes on Sheet S201 for design loading requirements and additional information.
- 11 Anchor girder truss to steel beam per Detail 7-S402.
- 12 Anchor column at end of tube beam to end of concrete masonry wall with adhesive anchors at Elevation 101-0, Elevation 104-4, and Elevation 107-8 per Detail 4-S402.
- 13 Support wood beam with face mount hanger that is screw anchored to face of solid grouted concrete masonry wall and strap top of wood beam to plates on top of concrete masonry wall per Section 7-S401.

ROOF FRAMING PLAN GENERAL NOTES:

1. See General Structural Notes on sheet S201 and S202 and specifications for additional notes and information.
2. Perimeter framing plan dimensions on exterior of building are to exterior face of veneer or exterior face of concrete masonry wall where masonry veneer does not occur, unless noted otherwise. See Architectural Drawings for dimensional location of interior walls. See the Architectural Drawings for roof overhang, eave, and soffit details. See the Architectural Drawings for door and window opening size, location, and elevation.
3. See Sheets S401 and S402 for typical framing details:
See Detail 15-S401 for Typical Roof Opening Detail for roof openings between pre-fabricated roof trusses.
See Detail 17-S401 for Typical Top Plate Splice Detail.
See Detail 13-S401 for Typical Ridge Detail and Detail 14-S401 for Typical Hip and Valley Detail and 2x6 blocking between roof framing at all hip and valley lines.
4. Pre-fabricated wood truss layout is schematic in nature and is not intended to indicate a specific quantity of trusses required. Truss Fabricator shall provide a specific truss layout and all trusses required to complete the roof framing. Truss Fabricator to coordinate truss location and geometry with duct work and any mechanical equipment in the attic. See Mechanical Drawings for additional information.
5. Truss fabricator to design all truss to truss connection hardware, typical.
6. Top of all interior non-load bearing masonry walls shall be braced to the structure per Details 10 and 11-S402, unless noted otherwise.
7. See Detail 18-S301 for Typical Masonry Wall Reinforcing and Grouting Detail.
8. See Detail 4-S301 for Typical Masonry Control Joint Details.
9. See Detail 5-S301 for Typical Masonry Jamb Details at Lintel Bearing.




BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed as to all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

DWA Dudley Williams and Associates, PA
2301 West 20th Street
Wichita, KS 67217-1514
316-263-7500 or www.dwa.com
17-045-01 5102 in 17-045/17-045(1)S-1X 7/7/2017 (40) (194)



REV	DESCRIPTION	DATE

Project Number: **16036**

Date: **7/7/17**

Project Name:

**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
**ROOF
FRAMING
PLAN**

Sheet:
S102

Of:

SPECIAL NOTES AND REQUIREMENTS REGARDING FOUNDATION SYSTEMS AND STRUCTURAL FRAMING SYSTEMS

- A. SLEEVES OR BLOCKOUTS IN FOUNDATION WALLS**
- Sleeves or blockouts 10 inches or greater in any direction must be approved prior to installing in any foundation wall.
 - Locate sleeves or blockouts where the edge of the opening closest to the top or bottom of the walls is 12 inches or greater, unless specifically approved otherwise.
 - Provide 2-#5 bars, 4'-0" longer than the opening dimension, on all sides of the opening in the walls, with the bars centered on the opening.
 - No sleeves or blockouts shall occur within the columns or pilasters cast integral with the walls. No sleeves or blockouts shall occur in the walls directly below the beam bearing points unless specifically approved otherwise.
 - Provide a minimum of 12 inches of concrete between the adjacent sleeves or blockouts unless specifically approved otherwise.
 - Cored openings shall meet the same requirements as the sleeved openings.

- B. SLEEVES OR BLOCKOUTS IN TRENCH FOOTINGS**
- Sleeves or blockouts 10 inches or greater in any direction must be approved prior to installing in any trench footings.
 - Locate sleeves or blockouts where the edge of the opening closest to the top or bottom of the trench footing is 12 inches or greater unless specifically approved otherwise.
 - Provide 2-#4 horizontal bars above and below the trench footing openings, one bar each face. Provide one additional trench footing strip placed with 2 inches to 3 inches each side of the trench footing sleeve or blockout for openings greater than 6 inches.
 - No sleeves or blockouts shall occur within the columns or pilasters cast integral with the trench footings.
 - Provide a minimum of 12 inches of concrete between the adjacent sleeves or blockouts unless specifically approved otherwise.
 - Cored openings shall meet the same requirements as sleeved openings.

C. MECHANICAL OR ELECTRICAL OPENINGS, SLEEVES, CONDUITS, OR CORED HOLES IN CONCRETE MASONRY WALLS

- All lintels shall be built into the concrete masonry walls as the walls are being constructed.
- Do not locate any masonry openings, sleeves, or cored holes directly below any joist or beam bearing plates unless specifically approved otherwise.
- Mechanical duct openings in the concrete masonry walls that occur below the roof structures shall be located such that the opening and the lintel occur completely below the bond beams at the roof framing member bearing elevation, unless specifically approved otherwise.
- Locate the top of all horizontal sleeves or cored holes in the concrete masonry walls that occur below the roof structures to provide a minimum 8 inch deep bond beam lintel below the roof framing member bearing elevation and above the sleeves or cored holes unless approved otherwise.
- Locate all horizontal sleeves or cored holes in the concrete masonry walls to provide a minimum of 8 inches of concrete masonry between adjacent sleeves or cored holes which are 4" or less in size and to provide 16 inches of concrete masonry between adjacent sleeves or cored holes which are greater than 4" in size, unless approved otherwise.
- Do not place any conduit in vertically reinforced and/or grouted masonry cores, unless specifically approved otherwise. Vertical conduit may pass through horizontal bond beams, excluding bond beam lintels and bond beam lintel bearing, unless noted otherwise.
- Multiple vertical conduits which exit the masonry wall horizontally at approximately the same elevation with a total width of more than 16 inches are considered wall openings. All recessed electrical panels in masonry walls are considered wall openings. Multiple horizontal sleeves and cored holes at approximately the same elevation which do not comply with Comment 5 of this section are considered openings. Provide lintel and masonry jamb reinforcing at these locations as indicated on the plans, lintel schedule, General Structural Notes, sections and details.

- Electrical panels recessed into masonry walls shall be submitted to the Architect/Engineer for review and additional structural requirements. Submittal shall include the proposed plan location, the actual masonry rough opening dimensions, the proposed elevation at the top of the electrical panel rough opening, and the quantity and size of the conduit above and below the electrical panel.

- Horizontal electrical conduit placed in masonry block walls shall have a maximum conduit size of 3/4 inch (0.922" maximum outside diameter) and the installation shall comply with the subsequently defined requirements. No conduit with a conduit size greater than 3/4 inch (0.922" maximum outside diameter) shall be installed horizontally in masonry walls unless specifically approved otherwise.

- Do not place any horizontal conduit in horizontal bond beams, unless specifically approved otherwise.
- Horizontal conduit within masonry walls shall be confined to the cores between the vertically reinforced and/or grouted masonry cores to the greatest extent possible. The 8 inch deep masonry course containing the horizontal conduit shall be grouted solid for the full horizontal length of the conduit.
- A single 3/4 inch conduit (0.922" maximum outside diameter) may pass horizontally through a solid grouted and/or vertically reinforced core at the jamb of a wall opening where required to connect to an electrical device above or below the wall opening.
- Notify Architect/Engineer of any required conduit installations which do not comply with the above criteria prior to the construction of the masonry wall.

D. EMBEDS, ANCHORS AND INSERTS IN STRUCTURAL MEMBERS AND SLABS

- The general, mechanical, and electrical contractors shall be responsible for the design of all supplemental framing systems required for the support of the architectural, mechanical, and electrical systems which are not detailed on the structural drawings.

E. DIMENSIONAL AND ELEVATION CHECK AND TOLERANCE

- As soon as possible after the completion of the noted items, the Contractor shall perform a dimensional and elevation check of the constructed items to confirm if the items have been built within an acceptable tolerance. The Contractor shall notify the Architect/Engineer for direction if the noted item have not been built within the specified tolerance.
- The placement of all anchor rods or embeds in the concrete foundation systems for the attachment of structural steel framing systems shall be checked for accuracy in the dimensional location and elevation. The acceptable tolerance in the placement of anchor rods and embeds cast into concrete for structural steel connections shall be as defined in ACI 308, Specification for Concrete Construction and Materials and Commentary Section 2.3, and the AISC Code of Standard Practice for Steel Building and Bridges Section 7. It is recommended that the check be performed prior to delivery of the fabricated structural steel members to the site, where ever possible, so that any required modifications or adjustments to the structural members can be made as directed by the Architect/Engineer in the shop rather than in the field. Field cutting to enlarge holes or modify framing members or connecting plates or angles shall not be performed prior to receiving direction from the Architect/Engineer.
- The placement of all reinforcing steel bars in cast-in-place concrete shall be checked to confirm that the specified or noted concrete coverage is being maintained on the reinforcing bars and tie wires. At all locations where the concrete surface in the completed building is exposed to view, exposed to the exterior, or exposed to a wet environment, the placement of the reinforcing bars and tie wires must be checked, modified where necessary, and approved prior to the placement of forms. All loose tie wires must be removed and the ends of all tie wires must be bent back into the concrete members. The reinforcing bar placement must be properly chaired or properly held in place to prohibit any displacement during the concrete placement.

TRENCH FOOTING SCHEDULE


MARK	TYPE	ELEV. BOTT.	ELEV. TOP	ELEV. LEDGE	DIMENSIONS		REF. SECTION	REMARKS
					T	A		
T1	1	96-0	99-4	-	1-6	-	8-5301	See Section 11-5301 at Door
T2	1	96-0	99-4	-	2-0	-	7-5301	See Section 11A-5301 at Door
T3	1	96-0	99-4	-	1-6	-	9-5301	
T4	1	96-0	99-4	-	1-6	-	10-5301	See Section 11-5301 at Door
T5	2	96-0	99-4	-	2-6	-	14-5301	
T6	2	96-0	99-4	-	3-6	-	14-5301	
T7	2	96-0	99-4	-	2-6	-	1-5302	
T8	2	96-0	99-4	-	3-0	-	1-5302	
T9	1	96-0	99-4	-	2-6	-	7-5301	See Section 12413-5301 at Glazing
T10	1	96-0	99-4	-	1-6	-	17-5301	

TRENCH FOOTING SCHEDULE REMARKS:

- See plan, schedule, and sections for formed concrete wall conditions, dimensions, and elevations above trench footing.

TRENCH FOOTING SCHEDULE NOTES:

- The scheduled trench footing width is the minimum structural width required. Where rigid insulation is required adjacent to the trench footing, increase the width of the excavation to allow for the structural width of the trench footing plus the thickness of the insulation. See Architectural Drawings for locations with foundation insulation.




TRENCH FOOTING SCHEDULE TYPES

WALL FOOTING AND FOUNDATION SCHEDULE

MARK	TYPE	FOOTING			FOUNDATION			REF. SECTION	REMARKS
		ELEV. TOP	WIDTH W	DEPTH D	ELEV. TOP	ELEV. LEDGE	T A		
W1	A	(A)	(A)	(A)	101-4	-	1-0	-	14-5301
W2	A	(A)	(A)	(A)	102-8	-	1-0	-	14-5301
W3	A	(A)	(A)	(A)	102-8	-	1-0	-	1-5302

WALL FOOTING AND FOUNDATION SCHEDULE REMARKS:

- See Trench Footing Mark and Schedule for trench footing dimensions and elevations.




WALL FOOTING AND FOUNDATION SCHEDULE TYPES

CONCRETE COLUMN AND FOOTING SCHEDULE


MARK	F1	F2	F3	F4	F5
	(1)	Reinforce as a	Reinforce as a		
COLUMN SIZE	-	20x20 Column	20x20 Column	32x32	32x32
ELEV. TOP COLUMN	-	99-4	99-4	110-0	110-0
COLUMN VERTS.	-	Footing Dowels	Footing Dowels	(B) #8x10-4	(B) #8
COLUMN TIES	-	(2)	(2)	(3)	(3)
ELEV. TOP FOOTING	99-4	99-4	99-4	99-4	See Section 4-5302
FOOTING SIZE	3-0x3-0x3-4	3-0x3-0x3-4	3-6x3-6x3-4	5-0x5-0x3-4	5-0x5-0x3-4
FOOTING BARS	(B) #5x2-6 4 Each Way	(B) #5x2-6 4 Each Way	(B) #5x3-0 4 Each Way	10-#6x4-6 5 Each Way	10-#6x4-6 5 Each Way
FOOTING DOWELS	Masonry Dowels	(4) #7x4-0 2-10 1-2	(4) #7x4-0 2-10 1-2	(B) #8x8-4 7-0 1-4	(B) #8x8-4 7-0 1-4

CONCRETE COLUMN AND FOOTING SCHEDULE REMARKS:

- Center pad footing below beam bearing location.
- #3 column ties, 4 at 3" o.c. at top of column with remainder at 12" o.c.
- #4 column ties, 1 at 3" at top of column with remainder at 12" o.c.



CONCRETE COLUMN DETAILS



SCHEMATIC COMPONENTS AND CLADDING WIND PRESSURE ZONES DIAGRAM

ROOF COMPONENTS AND CLADDING MINIMUM WIND DESIGN PRESSURES

ZONE	ALL ZONES	NO OVERHANG			OVERHANG	
		ZONE 1	ZONE 2	ZONE 3	ZONE 2	ZONE 3
WIND AREA (FT²)						
10	+16.6	-26.4	-45.9	-67.9	-53.7	-90.4
20	+15.1	-25.6	-42.2	-63.5	-53.7	-81.6
50	+13.2	-24.7	-37.4	-57.7	-53.7	-69.9
100	+11.7	-23.9	-33.7	-53.3	-53.7	-61.1

ROOF COMPONENTS AND CLADDING MINIMUM WIND DESIGN PRESSURE TABLE NOTES:


- Positive pressures act inward to the building envelope.
- Negative pressures act outward to the building envelope.
- The use of linear interpolation is permitted for wind areas not shown.
- Wind pressures indicated in table are gross ultimate wind pressures to be used with the load combinations defined in the edition of the ASCE 7 referenced by the IBC edition defined in the General Structural Notes.
- Wind areas for components and cladding shall be the wind area as defined in the edition of the ASCE 7 referenced by the IBC edition defined in the General Structural Notes.
- Roof joists shall be designed for tabulated gross uplift forces less dead load. The dead load to be used in the uplift calculations shall not exceed 10 psf after applying the appropriate allowable stress design or strength design reduction factor for the wind uplift load cases.

WALL COMPONENTS AND CLADDING MINIMUM WIND DESIGN PRESSURES

LOCATION	WALL			PARAPET			
	ZONE 4/5	ZONE 4	ZONE 5	ZONE 4		ZONE 5	
WIND AREA (FT²)				CASE A (PSF)	CASE B (PSF)	CASE A (PSF)	CASE B (PSF)
10	+28.8	-31.3	-38.6	+74.8	-60.1	+96.7	-67.4
50	+25.8	-28.3	-32.6	+63.2	-54.1	+83.5	-58.4
100	+24.5	-27.0	-30.0	+58.2	-51.5	+77.8	-54.5
200	+23.2	-25.7	-27.4	+56.9	-48.9	+76.5	-50.6
500	+21.5	-23.9	-23.9	+55.2	-45.4	+74.8	-45.4

WALL COMPONENTS AND CLADDING MINIMUM WIND DESIGN PRESSURES TABLE NOTES:

- Positive pressures act inward to the building envelope.
- Negative pressures act outward to the building envelope.
- The use of linear interpolation is permitted for wind areas not shown.
- Wind pressures indicated in table are gross ultimate wind pressures to be used with the load combinations defined in the edition of the ASCE 7 referenced by the IBC edition defined in the General Structural Notes.
- Wind areas for components and cladding shall be the wind area as defined in the edition of the ASCE 7 referenced by the IBC edition defined in the General Structural Notes.



BBN

BBN ARCHITECTS INC
228 FOYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

DWA Dudley Williams and Associates, PA
2301 Lee Ave Suite 200 Wichita, KS 67214
PH: 316-263-7914 www.dwa.com
17-048-01 5202 in 1/17-048/17-045/01/5-2X 1/7/2017 (40) (1-4)



REV	DESCRIPTION	DATE

Project Number:	16036
Date:	7/7/17
Project Name:	USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS
Project Address:	4290 COLUMBIAN ROAD WAMEGO, KS

Sheet Title:
NOTES, SCHEDULES, AND DETAILS

Sheet:
S202

A

B

C

D

LINTEL SCHEDULE

MARK	MEMBERS	TYPE	REMARKS
LA1	8" Deep Bond Beam Lintel with (2) #5 Cont. Reinf. Bars	A	
LB1	16" Deep Bond Beam Lintel with (4) #5 Cont. Reinf. Bars	B	
LB2	24" Deep Bond Beam Lintel with (4) #5 Cont. Reinf. Bars	B	
LC1	Lintel LB1 with Horizontal Bottom PL 5/16x15 and Continuous Vertical PL 3/8x6	C	①
LC2	Lintel LB2 with Horizontal Bottom PL 5/16x15 and Continuous Vertical PL 3/8x6	C	②

LINTEL SCHEDULE REMARKS:

- ① Stiffener plate 3/8x2 at 12" from each end of tee plate lintel and equally spaced at maximum 48" o.c. between unless noted otherwise. Weld to vertical and horizontal plates with 3/16" fillet welds all around.
- ② Bear built-up tee plate lintel 8" on to masonry veneer at each end. Provide notch in horizontal steel plate where lintel bears on concrete masonry wall (bear 1/4" onto CMU) per Detail 5-5301 to allow vertical wall opening jamb reinforcing to be continuous and uninterrupted by horizontal steel plate.

LINTEL SCHEDULE NOTES:

- TYPICAL AT ALL BOND BEAM LINTELS:** Extend bond beam lintels a minimum of 24" beyond concrete masonry jambs. Provide horizontal reinforcing with corner bars where 24" extension is not possible. Special U-shaped bond beam lintel block units shall be used for bottom course of all bond beam lintels. Knock-out or low web bond beam block units shall be used for all courses of bond beam lintels except for the bottom course. Properly shore all bond beam lintels during block and grout placement and all shores shall remain in place for a minimum of 7 days and until the grout has attained its specified compressive strength. Bond beam lintels shall be filled with grout for the entire depth and length of bond beam in one monolithic pour. Grout solid 2 cores (16" minimum) adjacent to opening below lintel bearing for full height of wall below lintel bearing. See Detail 1-5203 for built-up steel tee plate lintel details in masonry walls. See Detail 5-5301 for typical bond beam (and bond beam with built-up steel tee plate) lintel bearing and reinforcing placement at jambs of openings in masonry walls, unless indicated otherwise.
- Galvanize all exterior steel lintels.
- Build masonry veneer tight below lintel bottom plates at end of lintels for bearing prior to laying lintel supported masonry veneer.
- Provide continuous bond beam lintel (where bond beam lintel is required per schedule) over adjacent wall openings to create multiple span lintel condition where the masonry wall remaining between adjacent wall openings is less than or equal to 4'-0".
- Not all openings which require lintels are shown on Structural Drawings. Refer to the Architectural, Mechanical, and Electrical drawings for locations of additional openings in masonry walls. See the Architectural Drawings for size, location, and elevation of all wall openings. Determine the size, location, and elevation of all mechanical and electrical wall openings from the Mechanical and Electrical Drawings. (Verify the Mechanical and Electrical openings with the Mechanical and Electrical Contractors.) All lintels shall be built into masonry walls as the walls are being constructed.
- Provide lintels as indicated below for openings that are not shown on plans.

Typical Lintels Over Exterior Openings -

Provide Lintel LB1 at all openings 2'-8" or less in width in exterior concrete masonry walls, unless noted otherwise. Provide Lintel LC1 at all openings 2'-8" or less in width in exterior concrete masonry walls with masonry veneer, unless noted otherwise.

Typical Lintels Over Interior Architectural, Mechanical, or Electrical Openings-

Provide Lintel LA1 at all openings 3'-4" or less in width in new interior concrete masonry non-load bearing walls, unless noted otherwise.

Provide Lintel LB1 at all openings greater than 3'-4" and 5'-4" or less in width in new interior concrete masonry non-load bearing walls and at all openings 2'-8" or less in width in new interior concrete masonry load bearing walls, unless noted otherwise. The opening width must not occur directly below or within 1'-0" of a beam bearing point, unless approved otherwise.

Provide Lintel LB2 at all openings greater than 2'-8" and 4'-0" or less in width in new interior concrete masonry load bearing walls, unless noted otherwise. The opening width must not occur directly below or within 1'-0" of a beam bearing point, unless approved otherwise.

Provide a minimum of 24 inches of solid masonry between adjacent mechanical or electrical openings unless approved otherwise.

STEEL COLUMN SCHEDULE


MARK	S1	S2	S3
	①		
COLUMN SECTION	H564x4x1/2	H565x5x1/2	H566x3x1/2
BASEPLATE	PL 3/8x10x10	PL 3/8x11x11	PL 3/8x10x10
BASEPLATE DTL	A	A	B
ELEV. BOTTOM	99-6	99-6	99-6
GROUT	2"	2"	2"
ANCHOR RODS	(4) AR1	(4) AR2	(4) AR2

STEEL COLUMN SCHEDULE AND DETAIL NOTES:


- Base Plate Anchor Rods:
AR1 - 3/4"φx1-1 Galvanized Anchor Rod (6" projection)
AR2 - 3/4"φx1-1 Anchor Rod (6" projection)
- Base Plate Anchor Rod Hole Sizes:
Provide 1/16" holes in base plates for 3/4"φ anchor rods.

STEEL COLUMN SCHEDULE REMARKS:


- ① Galvanize column assembly and all associated hardware.



Base Plate A



Base Plate B



Anchor Rod AR2


BASE PLATE SCHEDULE DETAILS

BEARING PLATE SCHEDULE


MARK	MEMBERS	TYPE	REMARKS
BA1	PL 1x7x1-4 with (2) AR3	A	

BEARING PLATE SCHEDULE NOTES:


- Grout all block cores (2 block cores minimum, unless noted otherwise) solid below bearing plate for full height of wall. Bolt bearing plate to masonry wall. Field weld steel beam to bearing plate. Lay concrete masonry solid around beam bearing after installing beam where concrete masonry wall occurs either side of beam. See Detail 1-5402 for additional notes and information.
- Bearing Plate Anchor Rods:
AR3 - 3/4"φx1-1 Anchor Rod (4 1/2" projection)
- Bearing Plate Anchor Rod Hole Sizes:
Provide 1/16" diameter holes in bearing plates for 3/4" diameter anchor rods.




BEARING PLATE SCHEDULE DETAIL




① TYPICAL STEEL LINTEL DETAIL
No Scale



Anchor Rod AR1




Anchor Rod AR2



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.




DWA
Dudley Williams and Associates, PA
2301 West 40th Street, Suite 200 • Wichita, KS 67212-1514
316-263-7974 • www.dwa.com


17-048.01 5203 in 11/17-048/17-048.01/5-2X 7/7/2017 (40) (1/4)

REV	DESCRIPTION	DATE


Project Number: **16036**
Date: **7/7/17**
Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**
Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**
Sheet Title:
**SCHEDULES
AND DETAILS**
Sheet:
S203
Of:




TYPICAL DETAIL AT ALL FOUNDATION WALLS AND TRENCH FOOTINGS




NOTE: All Saw Cut Joints in Interior Floor Slabs Shall Use Soff-cut or Early Entry Dry-cutting Sawing System.




TYPICAL DETAIL



TYP. MASONRY E/J/CJ DETAILS



TYP. BOND BEAM LINTEL BEARING DETAILS



TYPICAL DETAIL

1 TYP. CORNER BAR DETAIL


2 TYP. SLAB JOINT DETAILS

3 TYPICAL DETAIL


4 TYP. MASONRY E/J/CJ DETAILS

5 TYP. BOND BEAM LINTEL BEARING DETAILS


6 TYPICAL DETAIL




7 SECTION




8 SECTION




9 SECTION




10 SECTION




11A SECTION




12 SECTION




13 SECTION




14 SECTION




15 SECTION




16 SECTION




17 SECTION




18 SECTION



19 SECTION




20 SECTION



21 SECTION

Typical Masonry Wall Reinforcing and Grouting Notes:


- Grout solid all noted block cores and all cores with vertical reinforcing bars. Grout shall attain a 2500 psi minimum 28 day compressive strength and shall have a 8 in. to 10 in. slump range.
- Grout shall be placed in maximum 24 in. grout lift heights and each lift height shall be consolidated by mechanical vibration during grout placement.
- Reconsolidate each grout lift height 5 to 15 minutes after initial grout placement by mechanical vibration. Initial grout lift height shall be consolidated prior to placement of additional grout lift to complete the grout pour height.
- The grout horizontal construction joint at each pour height shall stop a minimum of 1/2" below a block mortar joint, except at the top of the wall or at the block coursing below bond beams, beam bearing, or other similar locations. Adjust grout level after reconsolidation at the top of walls, below bond beams, below beam bearings, or other similar locations as required to attain the proper top of grout elevation.
- Use a small headed vibrator and only vibrate each grouted core for a few seconds during the consolidation and reconsolidation process.
- Mortar shall not project more than 1/4" from the face of the block into the block core in all block cores to be grouted. Clean out the block cores of all mortar droppings or excessive mortar projections prior to starting the grouting process.
- Provide horizontal joint reinforcing per specifications at 16" o.c. vertically, unless noted otherwise.
- Provide vertical masonry reinforcing and masonry dowels (in addition to bars at the defined spacing) at corners, jambs of openings, each end and at corners of masonry walls, and control joints as defined in the general structural notes.
- See Detail 4-5301 for Typical Masonry Expansion and Control Joint Details. See Detail 5-5301 for Typical Lintel Bearing Details.
- Center vertical masonry wall reinforcing bars in concrete masonry wall, unless noted otherwise.



- A** Masonry Dowel Embedment Length into Foundation System or Concrete Beam:
 - #4 Bars - 2'-0" Minimum
 - #5 Bars - 2'-0" Minimum
 - (Provide Standard 90° Hook Where Required Straight Embedment is Not Available)
- B** Masonry Vertical Bar Lap Splice Length at Each Grout Pour Height:
 - #4 Bars - 2'-0" Minimum
 - #5 Bars - 2'-6" Minimum

Contractor's Option: Vertical Masonry Reinforcing Bars May be Mechanical Spliced Rather Than Lap Spliced at the Contractor's Option. Mechanical Bar Splices shall be Dayton Superior D-310 Taper-lock Coupler System, Erico Lenton Taper Threaded Splicing System, or an Approved Equal.

18 TYP. WALL REINF. DETAIL




BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the intended result. All drawings and written material appearing herein contain the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

DWA Dudley Williams and Associates, PA
2301 West 4th Street, Suite 200 - Wichita, KS 67215-1514
316-263-7504 or www.dwa.com











REV	DESCRIPTION	DATE

Project Number: **16036**
Date: **7/7/17**
Project Name: **USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS**

Project Address: **4290 COLUMBIAN ROAD WAMEGO, KS**

Sheet Title: **FOUNDATION SECTIONS AND DETAILS**

Sheet: **S301**




BBN

BBN ARCHITECTS INC
228 FOYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

DWA Dudley Williams and Associates, PA
2301 West 4th Street, Suite 200 • Wichita, KS 67219-1514
316-263-7970 • www.dwa.com
17-045.01 5302 in 1/17-045/17-045.01/S-3X 7/7/2017 (40) (1-24)



REV	DESCRIPTION	DATE


















Project Number: **16036**
Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
**FOUNDATION
SECTIONS AND
DETAILS**

Sheet:
S302
OF




BBN

BBN ARCHITECTS INC
228 FOYNTA AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Includes as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

DWA Dudley Williams and Associates, PA
2301 West 42nd Street, Suite 200 - Wichita, KS 67215-1514
316-263-7500 or www.dwa.com
17-045-01 5401 in 17-045-017-045-015-4x 1/7/2017 (04) [114]




REV	DESCRIPTION	DATE

Project Number: **16036**
Date: **7/7/17**


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**
Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
**FRAMING
SECTIONS AND
DETAILS**


Sheet:
S401




1 TYPICAL FRAMING DETAILS
No Scale




2 TYPICAL FRAMING DETAILS
No Scale



3 TYPICAL STEPPED BOND BEAM DETAIL
No Scale




4 TYPICAL FRAMING DETAILS
No Scale




5 DETAIL
3/4" = 1'-0"




6 DETAIL
3/4" = 1'-0"




7 DETAIL
3/4" = 1'-0"



8 SECTION
3/4" = 1'-0"




9 DETAIL
No Scale



10 DETAIL
No Scale


Typical Top of Masonry Wall Bracing Detail
Contractor to Coordinate Brace Locations and Quantities

Typical Top of Masonry Wall Bracing Detail
Contractor to Coordinate Brace Locations and Quantities




Typical Top of Wall Brace Detail at Non-load Bearing Masonry Walls Which are Parallel to Wood Trusses, U.N.O.

10 SECTION
3/4" = 1'-0"



Typical Top of Wall Brace Detail at Non-load Bearing Masonry Walls Which are Perpendicular to Wood Trusses, U.N.O.



11 SECTION
3/4" = 1'-0"



BBN

BBN ARCHITECTS INC
228 FOYNT AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.



REV	DESCRIPTION	DATE

Project Number: **16036**
Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
**FRAMING
SECTIONS AND
DETAILS**

Sheet:
S402
Of:

ABBREVIATIONS:

THE FOLLOWING LIST OF ABBREVIATIONS MAY BE USED IN THE CONTRACT DOCUMENT DRAWINGS.

&	AND	MAX.	LIGHTWEIGHT CONCRETE
∠	ANGLE	MEGH.	MECHANICAL
⊙	AT	MFG.	MANUFACTURING
∅	DIAMETER	MFR.	MANUFACTURER
#	NUMBER OR POUND	MIN.	MINIMUM
		MIR.	MIRROR/MIRRORED
ACQST.	ACOUSTICAL	MISC.	MISCELLANEOUS
ADJ.	ADJUSTABLE	MTD.	MOUNTED
A.F.F.	ABOVE FINISHED FLOOR	MTL.	METAL
ALUM.	ALUMINUM	N/A	NOT APPLICABLE
APPROX.	APPROXIMATE	N.I.C.	NOT IN CONTRACT
ARCH.	ARCHITECTURAL	NO.	NUMBER
		NOM.	NOMINAL
BD.	BOARD	N.P.S.	NOMINAL PIPE STANDARD
BLDG.	BUILDING	N.T.S.	NOT TO SCALE
BLCKG.	BLOCKING		
B.O.	BOTTOM OF	O.C.	ON CENTER
BRG.	BEARING	O.D.	OUTSIDE DIAMETER/DIMENSION
B.S.	BOTH SIDES	O.H.	OPPOSITE HAND
℄	CENTERLINE	OPNG.	OPENING
CH.	CHANNEL	OVHD.	OVERHEAD
C.J.	CONTROL JOINT	OZ.	OUNCE
C.L.G.	CEILING		
C.M.U.	CONCRETE MASONRY UNIT	FL.	FLUTE
CONC.	CONCRETE	FLBS.	FLUISING
CONN.	CONNECTION	PLYND.	PLYWOOD
CONSTR.	CONSTRUCTION	POL.	POLISHED
CONT.	CONTINUOUS	FR.	FAIR
CONTR.	CONTRACTOR	PT.	POINT
CTR.	CENTER	PTD.	PAINTED
		QTY.	QUANTITY
DBL.	DOUBLE	R.	RISER OR RADIUS
DIA.	DIAMETER	R.C.P.	REFLECTED CEILING PLAN
DM.	DIMENSION	RE	REFERENCE
DN.	DOWN	RENF.	CONNECTION
DR.	DOOR	REQD.	REQUIRED
DWS.	DRAWING	REV.	REVISION OR REVERSED
		RM.	ROOM
EA.	EACH	R.O.	ROUGH OPENING
E.F.	EACH FACE	S.C.	SOLID CORE OR SEALED CONCRETE
EL.	ELEVATION		
ELEG.	ELECTRICAL	SCHED.	SCHEDULE
ELEV.	ELEVATOR	SECT.	SECTION
EQ.	EQUAL	S.F.	SQUARE FOOT
EQUIP.	EQUIPMENT	SHT.	SHEET
E.S.	EACH SIDE	SM.	SIMILAR
EXP.	EXPANSION	SPEC.	SPECIFICATION(S)
EXIST.	EXISTING	SP. HD.	SPRINKLER HEAD
EXT.	EXTERIOR	SQ.	SQUARE
EYN.	EACH WAY	S.S.	STAINLESS STEEL
		STD.	STANDARD
FIN.	FINISH	STL.	STEEL
FL.	FLOOR	STO.	STORAGE
F.O.F.	FACE OF FINISH	STRUCT.	STRUCTURAL
F.O.S.	FACE OF STUD	SQ. YD.	SQUARE YARD
FR.	FRAME	SYS.	SYSTEM
FT.	FOOT OR FEET		
FUR.	FURRING	T	TREAD
F.D.	FLOOR DRAIN	TEL.	TELEPHONE
		TEMP.	TEMPORARY
GA.	GAUGE	T.O.	TOP OF
GALV.	GALVANIZED	T.O.D.	TOP OF DECK
GL.	GLASS	T.O.S.	TOP OF SLAB/STEEL
G.S.	GROUT SOLID	T.O.W.	TOP OF WALL
GYP. BD.	GYP. BOARD	TV	TELEVISION
		TV.	TYPICAL
HDA.	HARDWARE	U.N.O.	UNLESS NOTED OTHERWISE
HWD.	HARDWOOD	VERT.	VERTICAL
H.M.	HOLLOW METAL		
HORIZ.	HORIZONTAL		
HT.	HEIGHT		
ID.	INSIDE DIAMETER/DIMENSION	W	WITH
IN.	INCH	W/I	WITHIN
INFO.	INFORMATION	W/O	WITHOUT
INSUL.	INSULATION	WOD.	WOOD
INT.	INTERIOR	WDL.	WINDOW
		WHT.	WEIGHT
L	LONG/LENGTH		
L.T. (LTS.)	LIGHT/LIGHTING		
L.M.C.	MAXIMUM		

MATERIAL IDENTIFICATION KEY:

	CONCRETE
	CONCRETE MASONRY UNITS
	PRECAST CONCRETE
	EARTH
	STEEL
	DISCONTINUOUS LUMBER
	CONTINUOUS LUMBER
	RIGID INSULATION
	BLANKET INSULATION
	GYP. BOARD
	PLYWOOD
	FINISHED WOOD
	GRANULAR FILL
	METAL STUD FRAMING
	WOOD STUD FRAMING


DIMENSIONING CRITERIA:

ALL DRAWINGS ARE INTENDED TO BE COMPLIMENTARY. NOTIFY THE ARCHITECT OF ANY DIMENSIONING DISCREPANCY PRIOR TO PROCEEDING.


DIMENSIONS ARE AS IDENTIFIED ON THE DOCUMENTS AND AS ESTABLISHED BY CRITERIA. THIS INVOLVES ESTABLISHING TYPICAL RULES GOVERNING PARTITION LOCATIONS AND THEN DIMENSIONING ONLY THE EXCEPTION TO THESE RULES. TYPICAL DIMENSIONING CRITERIA ARE OUTLINED BELOW.

COLUMN IDENTIFICATION DETAILS WILL GOVERN ALL DIMENSIONS AND FEIN DIMENSIONS WILL BE SHOWN ON THE SMALL SCALE PLANS.


A. COLUMN GRIDS ARE DRAWN ACCORDINGLY:




B. PARTITIONS CENTERED ON COLUMN OR GRID LINES WILL NOT BE DIMENSIONED ON THE PLANS, BUT DRAWN ACCORDINGLY:




C. PARTITIONS WITH THE FINISHED FACE FLUSH WITH THE COLUMN OR GRID LINE WILL NOT BE DIMENSIONED ON THE PLANS, BUT WILL BE DRAWN ACCORDINGLY:



D. PARTITIONS CENTERED ON WINDOW MULLIONS WILL NOT BE DIMENSIONED ON PLANS, BUT WILL BE DRAWN ACCORDINGLY:




E. PARTITIONS WITH FINISHED FACE ON THE COLUMN OR GRID LINES WILL NOT BE DIMENSIONED ON THE PLANS, BUT WILL BE DRAWN ACCORDINGLY:




F. FOR OPENINGS IN PARTITIONS OR WALLS:

- WHEN ONE OCCURS AT A COLUMN OR GRID LINE, NO DIMENSIONS WILL BE SHOWN ON THE PLANS; THE OPENING WIDTH WILL BE ESTABLISHED BY EITHER CRITERIA OR SCHEDULES.
- WHEN NEITHER JAMB OCCURS AT A PARTITION INTERSECTION, AT A COLUMN OR GRID LINE, ONE JAMB WILL BE LOCATED DIMENSIONALLY BY THE DETAIL.
- WHEN ONE JAMB IS LOCATED BY AN INTERSECTING PARTITION, THE FOLLOWING DIAGRAM APPLIES:



- WHEN ONE JAMB IS LOCATED BY A COLUMN, THE FOLLOWING DIAGRAM APPLIES:




6. STUD PARTITIONS ARE DIMENSIONED FROM THE FACE OF ONE UNIT TO THE FACE OF ANOTHER UNIT. AT EXTERIOR WALLS DIMENSIONS ARE FROM FACE OF SHEATHING TO FACE OF ANOTHER UNIT.


H. MASONRY PARTITIONS ARE DIMENSIONED FROM THE NOMINAL FACE OF C.M.U., BRICK OR STONE TO THE FACE OF ANOTHER UNIT.

GRAPHIC SYMBOLS/STANDARDS:


A. COLUMN AND/OR GRID LINES:



B. FLOOR PLAN MATCHLINE SYMBOL:




C. CENTERLINE SYMBOL:




D. BAR GRAPH SYMBOL:




E. NORTH ARROW:




F. SPECIFICATION SECTION REFERENCE SYMBOL:




G. SPOT ELEVATION SYMBOL:




H. ELEVATION REFERENCE SYMBOL:




I. DETAIL REFERENCE SYMBOL:




J. INTERIOR ELEVATION REFERENCE SYMBOL:



K. BUILDING SECTION REFERENCE SYMBOL:



L. DETAIL REFERENCE SYMBOL:



M. DETAIL REFERENCE SYMBOL:



N. WINDOW REFERENCE SYMBOL:




O. ROOM NUMBER/NAME SYMBOL:

- THE FIRST NUMERAL OF A ROOM NUMBER ACTS AS A FLOOR LEVEL INDICATOR, STARTING WITH '0' AT THE BASEMENT LEVEL AND WORKING NUMERICALLY UP.

P. ACCESSORY REFERENCE SYMBOL:



Q. WALL PARTITION TYPE SYMBOL: (SEE WALL TYPES)




R. EXISTING ASSEMBLY




S. REVISIONS SYMBOLS:




T. DETAIL NOTE SYMBOL:



U. RATED WALL CONSTRUCTION SYMBOLS:




V. FIRE EXTINGUISHER IDENTIFICATION SYMBOLS:



W. CEILING IDENTIFICATION SYMBOLS:

- SEE M.E.P. DRAWINGS FOR FIXTURE SPECIFICATIONS.



X. CEILING REFERENCE SYMBOLS:



Y. PLAN SYMBOLS:





GENERAL NOTES:

- NONE TO ALL OF THE LISTED CRITERIA, SYMBOLS, ETC. MAY OR MAY NOT BE USED IN THIS SET OF CONSTRUCTION DOCUMENTS.
- THE CONTRACTOR IS RESPONSIBLE FOR PRODUCING WEATHER-TIGHT CONSTRUCTION, DETAILS AND OMISSIONS TO THE DRAWINGS NOTWITHSTANDING.
- ALL FINISH COLORS, TEXTURE, AND PATTERNS TO BE SELECTED BY THE ARCHITECT AND APPROVED PRIOR TO INSTALLATION.
- ANY PIPE OR CONDUIT PENETRATION THRU EXTERIOR CONSTRUCTION SHALL BE SEALED AT BOTH SIDES FOR A WATER-TIGHT CONDITION, OR FOR FIRE STOP ASSEMBLIES THROUGH RATED WALLS.
- ALL FLOORS WITH DRAINS SHALL HAVE A MINIMUM OF 1/8" PER FOOT SLOPE TO DRAIN, U.N.O..
- CONTRACTOR SHALL INVESTIGATE, VERIFY, AND BE RESPONSIBLE FOR ALL EXISTING CONDITIONS AND NEW DIMENSIONS OF THE PROJECT AND CONFIRM SUCH TO BE APPROPRIATE AND COMPATIBLE WITH NEW CONSTRUCTION. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT OF ANY DISCREPANCY FOR CLARIFICATION OR ABOUT ANY CONDITION REQUIRING MODIFICATION OR CHANGE BEFORE PROCEEDING WITH THE WORK.
- ALL EXPOSED C.M.U. CORNERS TO BE BULL NOSE. COORDINATE EXCEPTIONS WITH ARCHITECT.

NOTES- FULL LIST	
3.1	CONCRETE SLAB ON GRADE- SEE STRUCTURAL DRWS.
3.3	EXTERIOR CONCRETE PAVEMENT- SEE CIVIL DRWS.
3.6	CONCRETE FOUNDATION- SEE STRUCTURAL DRWS.
3.9	CONCRETE PAVEMENT- SIDEWALK
3.4	GAST-FINISH CONCRETE
3.10	CONCRETE REVEAL- 1"
3.11	CONCRETE MON STRIP- 10" WIDE
3.12	CONCRETE COLUMN
3.13	CONCRETE RETAINING WALL
4.1	5' C.M.U.
4.2	6' C.M.U. BOND BEAM
4.3	12' C.M.U.
4.4	12' C.M.U. BOND BEAM
4.5	MASONRY TE
4.6	SOLID GROUT
4.7	HORIZONTAL REINFORCING- SEE STRUCTURAL DRWS
4.8	THRU-WALL FLASHING WITH DRIP EDGE
4.9	MORTAR
4.10	4" BURNISHED BLOCK VENEER
4.11	MASONRY CONTROL JOINT
4.12	CAVITY DRAINAGE MATERIAL
5.4	STEEL REINFORCING
5.6	STEEL ANGLE- SEE STRUCTURAL DRWS.
5.7	STEEL TIE- SEE STRUCTURAL
5.13	STEEL MISC. CHANNEL- SEE STRUCTURAL DRWS.
5.14	STEEL COLUMN- SEE STRUCTURAL DRWS.
5.15	STEEL LINTEL- SEE STRUCTURAL
5.14	STEEL PLATE- SEE STRUCTURAL
5.20	ALUMINUM FENCE
6.1	1/2" PLYWOOD SHEATHING- VERIFY WITH STRUCTURAL
6.3	4" PLYWOOD SHEATHING- VERIFY WITH STRUCTURAL
6.6	CUSTOM CASEWORK
6.9	WOOD BLOCKING
6.10	3/4" CEMENTITIOUS FACIA- PAINTED
6.11	WOOD TRUSSES- SEE STRUCTURAL
6.12	PBL ROOF BEAM- SEE STRUCTURAL
6.13	3/4" WOOD TRIM- PAINTED
1.1	JOIST SEALANT
1.2	BACKER ROD AND SEALANT
1.5	WATERPROOF MEMBRANE
1.6	2" RIGID WALL INSULATION
1.11	RIDGE VENT
1.9	METAL SOFFIT DECK- VENTED
1.4	SHEET METAL FLASHING
1.11	METAL SOFFIT DECK
1.10	TERMINATION BAR
1.13	VAPOR BARRIER
1.14	SPANDREL INSULATION
1.15	CELLULOSE INSULATION
1.16	ACOUSTIC BATT INSULATION
1.18	ACOUSTIC MAT MEMBRANE
1.20	ACOUSTIC SEALANT
1.21	8' X 8' DOWNSPOUT
1.22	E.I.P. S. VENEER
1.23	E.I.P. S. REVEAL- SEE DETAIL
1.24	2" RIGID FOUNDATION INSULATION
1.29	COMPOSITION ASPHALT SHINGLES
1.26	5" GUTTER
1.27	4' X 4' DOWNSPOUT- TIE INTO DRAINS- SEE CIVIL
1.28	EXPANSION JOINT- PAVEMENT
1.30	EXPANSION JOINT- WALL
1.31	WALL DRAINAGE BOARD
0.1	ALUMINUM STOREFRONT
0.2	ALUMINUM STOREFRONT DOOR
0.3	HOLLOW METAL DOOR
0.4	HOLLOW METAL FRAME
0.5	ALUMINUM BRAKE METAL
0.6	GLASS TYPE 1- CLEAR INSL. TEMPERED
0.4	GLASS TYPE 4- CLEAR INSL. TEMPERED SPANDREL GLASS
0.10	GLASS TYPE 6- CLEAR
0.14	ALUMINUM STOREFRONT DEFLECTION RECEPTOR
0.15	THRESHOLD
0.16	OVERHEAD COILING DOOR- MOTORIZED
0.17	OVERHEAD ALUMINUM SLAT COUNTER DOOR
4.1	5/8" TYPE X GYP. BD. IMPACT RESISTANT
4.2	5/8" TYPE X GYP. BD.
4.3	5/8" TYPE X GYP. BD. MOISTURE RESISTANT
4.4	1 1/2" METAL STUDS
4.5	2" X 2" METAL STUDS
4.6	6" METAL STUDS
4.1	TYPE 1 ACOUSTICAL CEILING TILE
4.2	TYPE 1 SUSPENDED CEILING SYSTEM
4.11	INTERIOR EPOXY PAINT
4.14	RESILIENT BASE
4.15	CARPET TILE
4.16	EPOXY RESIN FLOORING

NOTES- FULL LIST	
4.17	EPOXY RESIN BASE 5'
4.10	SEALED CONCRETE
4.20	POWDER COATED STEEL CORNER GUARD- 2' X 2' ANGLE
10.1	36" GRAB BAR
10.2	42" GRAB BAR
10.3	PAPER TOWEL DISPENSER- OWNER PROVIDED- N.I.C.
10.4	SOAP DISPENSER- OWNER PROVIDED- N.I.C.
10.10	FIRE EXTINGUISHER CABINET
10.13	MARKER BOARD
10.14	MIRROR- 10' X 36"
10.15	TOILET PARTITION
10.16	BBY CHANGING STATION
10.17	WALL SHELF
10.18	EXTERIOR SIGNAGE
10.20	48" GRAB BAR
10.21	SHOWER CURTAIN ROD, HOOKS
10.22	ATHLETIC LOCKERS
10.23	TWO TIER LOCKERS
10.24	LOCKER ROOM BENCH
10.25	FULL LENGTH MIRROR- 24' X 60"
10.26	PROJECTIONS SCREEN- 16.4' X 4.5'
12.1	TRAINING TABLE- PROVIDED BY OWNER
12.2	STACKABLE CHAIRS- PROVIDED BY OWNER
22.1	DUCTWORK- SEE MECH DRWS.
22.2	TOILET- SEE PLUMBING DRWS.
22.5	LAVATORY- SEE PLUMBING DRWS.
22.4	SERVICE SINK- SEE PLUMBING DRWS.
22.5	URINAL- SEE PLUMBING DRWS.
22.7	FLOOR DRAIN- SEE PLUMBING DRWS.
22.8	SHOWER- SEE PLUMBING DRWS. - RECESS SLAB FOR DRAIN.
23.1	DUCTWORK- SEE MECH DRWS.
23.2	MECHANICAL EQUIPMENT- SEE MECH. DRWS.
23.3	SUPPLY AIR DEVICE- SEE MECH DRWS.
23.4	RETURN AIR DEVICE- SEE MECH DRWS.
26.1	LIGHT FIXTURE- SEE ELEG. DRWS.
31.1	GRAVEL FILL
31.2	4" DRAIN TILE- DRAIN TO DAYLIGHT

TOILET ACCESSORIES KEY:




BBN


BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed to all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

REV	DESCRIPTION	DATE




NOTES	
4.1	8" C.M.U.
4.7	HORIZONTAL REINFORCING- SEE STRUCTURAL DRWG
T.16	ACOUSTIC BATT INSULATION
T.18	ACOUSTIC MAT MEMBRANE
T.20	ACOUSTIC SEALANT
9.1	5/8" TYPE X GYP. BD. IMPACT RESISTANT
9.5	3-5/8" METAL STUDS
9.6	6" METAL STUDS



BBN

BBN ARCHITECTS INC
228 POYNIZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.



WALL TYPES
1 1/2" = 1'-0"

REV	DESCRIPTION	DATE



Project Number: **16036**

Date: **7/7/17**


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**


Sheet Title:
WALL TYPES

Sheet:
A003


OF:



B5
A102
ENLARGED RESTROOM PLAN
1/4" = 1'-0"




B3
A102
ENLARGED LOCKERS 118 AND
RESTROOM PLAN
1/4" = 1'-0"




A2
A102
ENLARGED OFFICIALS RESTROOM
1/4" = 1'-0"

B2
A102
STEEL TO MASON COLUMN DETAIL - PLAN
1" = 1'-0"




C5
A102
ENLARGED PLAN- ROOM 106,107,111,
AND 112
1/4" = 1'-0"



NORTH
FLOOR PLAN
1/8" = 1'-0"

NOTES

- 3.1 CONCRETE- SLAB ON GRADE- SEE STRUCTURAL DRWG.
- 3.12 CONCRETE COLUMN
- 3.15 CONCRETE RETAINING WALL
- 4.8 SOLID GROUT
- 4.10 4" BURNISHED BLOCK VENEER
- 4.11 MASONRY CONTROL JOINT
- 5.14 STEEL COLUMN- SEE STRUCTURAL DRWG.
- 5.20 ALUMINUM FENCE
- 7.21 4" X 4" DOWNSPOUT- TIE INTO DRAINS- SEE CIVIL
- 9.1 5/8" TYPE 'X' GYP. BD. IMPACT RESISTANT
- 10.1 36" GRAB BAR
- 10.2 42" GRAB BAR
- 10.3 PAPER TOWEL DISPENSER- OWNER PROVIDED- N.I.C.
- 10.4 SOAP DISPENSER- OWNER PROVIDED- N.I.C.
- 10.10 FIRE EXTINGUISHER CABINET
- 10.13 MARKER BOARD
- 10.14 MIRROR- 18" X 36"
- 10.15 TOILET PARTITION
- 10.16 BABY CHANGING STATION
- 10.11 WALL SHELF
- 10.20 48" GRAB BAR
- 10.21 SHOWER CURTAIN, ROD, HOOKS
- 10.22 ATHLETIC LOCKERS
- 10.23 TWO TIER LOCKERS
- 10.24 LOCKER ROOM BENCH
- 10.25 FULL LENGTH MIRROR- 24" X 60"
- 22.1 DRINKING FOUNTAIN- SEE PLUMBING DRWG.
- 22.2 TOILET- SEE PLUMBING DRWG.
- 22.3 LAVATORY- SEE PLUMBING DRWG.
- 22.4 SERVICE SINK- SEE PLUMBING DRWG.
- 22.5 URINAL- SEE PLUMBING DRWG.
- 22.7 FLOOR DRAIN- SEE PLUMBING DRWG.
- 22.8 SHOWER- SEE PLUMBING DRWG - RECESS SLAB FOR DRAIN.
- 25.2 MECHANICAL EQUIPMENT- SEE MECH. DRWG.



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unaltered work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

REV	DESCRIPTION	DATE



Project Number: **16036**
Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**



Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:

FLOOR PLAN


Sheet:
A102

OF:




NOTES


- 4.1 8" C.M.U.
- 4.2 8" C.M.U. BOND BEAM
- 5.14 STEEL COLUMN- SEE STRUCTURAL DRWG.
- 6.0 WOOD BLOCKING
- 7.1 JOINT SEALANT
- 7.0 METAL SOFFIT DECK- VENTED
- 7.11 METAL SOFFIT DECK
- 7.13 VAPOR BARRIER
- 7.15 CELLULOSE INSULATION
- 7.16 ACOUSTIC BATT INSULATION
- 7.26 5" GUTTER
- 7.27 4" X 4" DOWNSPOUT- TIE INTO DRAINS- SEE CIVIL
- 8.17 OVERHEAD ALUMINUM SLAT COUNTER DOOR
- 9.1 5/8" TYPE 'X' GYP. BD. IMPACT RESISTANT
- 9.2 5/8" TYPE 'X' GYP. BD.
- 9.3 5/8" TYPE 'X' GYP. BD. MOISTURE RESISTANT
- 9.4 1 5/8" METAL STUDS
- 9.5 3-5/8" METAL STUDS
- 9.7 TYPE 1 ACOUSTICAL CEILING TILE
- 9.9 TYPE 1 SUSPENDED CEILING SYSTEM
- 10.26 PROJECTIONS SCREEN- 16-8" X 4.5"
- 23.1 DUCTWORK-SEE MECH DRWG.
- 23.3 SUPPLY AIR DEVICE-SEE MECH DRWG.
- 23.4 RETURN AIR DEVICE-SEE MECH DRWG.
- 26.1 LIGHT FIXTURE-SEE ELEC. DRWG.




B1
A103
DETAIL @ PROJECTION SCREEN
3" = 1'-0"




C3
A103
SOFFIT DETAIL @
3/4" = 1'-0"




C2
A103
RESTROOM SOFFIT DETAIL
3/4" = 1'-0"




C1
A103
DETAIL @ BATHROOM SOFFIT
3/4" = 1'-0"



D2
A103
DETAIL @ TYPICAL GYP. TEARAWAY
3" = 1'-0"



D1
A103
ACT TO WALL DETAIL
3" = 1'-0"



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

REV	DESCRIPTION	DATE
-----	-------------	------



Project Number: **16036**

Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:


**REFLECTED
CEILING PLAN**

Sheet:

A103

OF:


NOTES	
T.25	COMPOSITION ASPHALT SHINGLES
T.26	5" GUTTER
T.27	4" X 4" DOWNSPOUT- TIE INTO DRAINS- SEE CIVIL



BBN

BBN ARCHITECTS INC
 228 POYNIZ AVENUE
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912 - FAX: 785-776-0944
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.



NORTH
 Site Plan - Roof
 1/8" = 1'-0"

A
 B
 C

REV	DESCRIPTION	DATE



Project Number: **16036**

Date: **7/7/17**

Project Name:
**USD 320 SPORTS
 COMPLEX LOCKER
 AND CONCESSIONS**


Project Address:
**4290 COLUMBIAN ROAD
 WAMEGO, KS**

Sheet Title:
ROOF PLAN


Sheet:
A104

OF:


NOTES



A4 BUILDING SECTION- EAST-WEST
1/8" = 1'-0"



C4 BUILDING SECTION- NORTH-SOUTH
1/8" = 1'-0"



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

REV	DESCRIPTION	DATE



Project Number: **16036**

Date: **7/7/17**


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**

Sheet Title:
**BUILDING
SECTIONS**

Sheet:
A301

OF:



BBN

BBN ARCHITECTS INC
 228 POYNTZ AVENUE
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912 FAX: 785-776-0944
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

NOTES	
3.1	CONCRETE- SLAB ON GRADE- SEE STRUCTURAL DRWG.
3.6	CONCRETE FOUNDATION- SEE STRUCTURAL DRWG.
3.8	CONCRETE PAVEMENT- SIDEWALK
4.1	8" C.M.U.
4.2	8" C.M.U. BOND BEAM
4.4	12" C.M.U. BOND BEAM
6.8	WOOD BLOCKING
6.10	3/4" CEMENTITIOUS FACIA- PAINTED
6.11	WOOD TRUSSES- SEE STRUCTURAL
7.5	WATERPROOF MEMBRANE
7.6	2" RIGID WALL INSULATION
7.9	SHEET METAL FLASHING
7.11	METAL SOFFIT DECK
7.15	CELLULOSE INSULATION
7.22	E.I.F.S. VENEER
7.25	COMPOSITION ASPHALT SHINGLES
7.26	5" GUTTER
7.31	WALL DRAINAGE BOARD
8.3	HOLLOW METAL DOOR
4.3	5/8" TYPE 'X' GYP. BD. MOISTURE RESISTANT
31.1	GRAVEL FILL
31.2	4" DRAIN TILE-DRAIN TO DAYLIGHT

A

B

C

REV	DESCRIPTION	DATE



Project Number: **16036**

Date: **7/7/17**

Project Name:
**USD 320 SPORTS
 COMPLEX LOCKER
 AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
 WAMEGO, KS**


Sheet Title:

WALL SECTIONS


Sheet: **A302**

OF:


OF:




**A5
 A302** EAST RESTROOM ENTRY SOFFIT
 1 1/2" = 1'-0"




**D4
 A302** WALL SECTION 4
 3/4" = 1'-0"



**D3
 A302** WALL SECTION 2
 3/4" = 1'-0"




**D2
 A302** WALL SECTION 3
 3/4" = 1'-0"



**D5
 A302** WALL SECTION 3
 3/4" = 1'-0"


NOTES	
3.1	CONCRETE- SLAB ON GRADE- SEE STRUCTURAL DRWG.
3.6	CONCRETE FOUNDATION- SEE STRUCTURAL DRWG.
3.11	CONCRETE MOW STRIP-18" WIDE
4.1	8" C.M.U.
5.7	STEEL TUBE- SEE STRUCTURAL
5.14	STEEL COLUMN- SEE STRUCTURAL DRWG.
7.5	WATERPROOF MEMBRANE
7.9	SHEET METAL FLASHING
7.22	E.I.P.S. VENER
7.23	E.I.P.S. REVEAL- SEE DETAIL
7.24	2" RIGID FOUNDATION INSULATION
7.51	WALL DRAINAGE BOARD
D.1	ALUMINUM STOREFRONT
4.1	5/8" TYPE X GYP. BD. IMPACT RESISTANT
4.2	5/8" TYPE X GYP. BD.
3.1.1	GRAVEL FILL
3.1.2	4" DRAIN TILE-DRAIN TO DAYLIGHT




BBN

BBN ARCHITECTS INC
 228 POYNTZ AVENUE
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912 - FAX: 785-776-0944
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.



2 Section 2
 A303 3/4" = 1'-0"



1 Section 1
 A303 3/4" = 1'-0"

A

B

C

D

REV	DESCRIPTION	DATE



Project Number: 16036

Date: 7/7/17


Project Name:
**USD 320 SPORTS
 COMPLEX LOCKER
 AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
 WAMEGO, KS**


Sheet Title:
**WALL
 SECTIONS**

Sheet:
A303


OF:



A5 DETAIL @ WEST WALL RAKE
A501 1 1/2" = 1'-0"




A4 DETAIL @ NORTH WALL SOFFIT
A501 1 1/2" = 1'-0"




A3 DETAIL @ SOUTH SOFFIT
A501 1 1/2" = 1'-0"

NOTES


3.1	CONCRETE- SLAB ON GRADE- SEE STRUCTURAL DRWG.
3.3	EXTERIOR CONCRETE PAVEMENT- SEE CIVIL DRWG.
3.6	CONCRETE FOUNDATION- SEE STRUCTURAL DRWG.
3.8	CONCRETE PAVEMENT- SIDEWALK
3.11	CONCRETE MON STRIP-18" WIDE
4.1	2" G.M.U.
4.2	8" G.M.U. BOND BEAM
4.6	SOLID GROUT
4.8	THRU-WALL FLASHING WITH DRIP EDGE
4.10	4" BURNISHED BLOCK VENEER
5.14	STEEL COLUMN- SEE STRUCTURAL DRWG.
5.15	STEEL LINTEL- SEE STRUCTURAL
6.1	1/2" PLYWOOD SHEATHING- VERIFY WITH STRUCTURAL
6.3	3/4" PLYWOOD SHEATHING- VERIFY WITH STRUCTURAL
6.8	WOOD BLOCKING
6.10	3/4" CEMENTITIOUS FACIA- PAINTED
6.11	WOOD TRUSSES- SEE STRUCTURAL
6.12	PSL ROOF BEAM- SEE STRUCTURAL
6.13	3/4" WOOD TRIM- PAINTED
7.5	WATERPROOF MEMBRANE
7.6	2" RIGID WALL INSULATION
7.7	RIDGE VENT
7.8	METAL SOFFIT DECK- VENTED
7.4	SHEET METAL FLASHING
7.11	METAL SOFFIT DECK
7.13	VAPOR BARRIER
7.15	CELLULOSE INSULATION
7.22	E.I.P.S. VENEER
7.24	2" RIGID FOUNDATION INSULATION
7.25	COMPOSITION ASPHALT SHINGLES
7.26	5" GUTTER
7.27	EXPANSION JOINT- PAVEMENT
7.31	WALL DRAINAGE BOARD
8.1	ALUMINUM STOREFRONT
8.3	HOLLOW METAL DOOR
8.4	HOLLOW METAL FRAME
8.15	THRESHOLD
8.17	OVERHEAD ALUMINUM SLAT COUNTER DOOR
9.1	5/8" TYPE X GYP. BD. IMPACT RESISTANT
9.2	5/8" TYPE X GYP. BD.
9.11	GRAVEL FILL
9.12	4" DRAIN TILE-DRAIN TO DAYLIGHT




B5 RIDGE DETAIL
A501 1 1/2" = 1'-0"




B4 DETAIL @ CONCESSIONS COLUMNS
A501 1" = 1'-0"




B3 DETAIL @ FOUNDATION - COLUMN
A501 1 1/2" = 1'-0"




B2 DETAIL @ SOUTH WALL FOUNDATION
A501 1 1/2" = 1'-0"




D5 DETAIL @ NORTH FOUNDATION WALL
A501 1 1/2" = 1'-0"




D4 DETAIL @ NORTH WALL FOUNDATION
A501 1 1/2" = 1'-0"




C3 CONCESSIONS SOFFIT AND CEILING COUNTER DOOR DETAIL
A501 3/4" = 1'-0"



D3 DETAIL @ FOUNDATION - EAST RESTROOM DOOR
A501 1 1/2" = 1'-0"



D1 DETAIL @ WEST WALL FOUNDATION
A501 1 1/2" = 1'-0"



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

REV	DESCRIPTION	DATE



Project Number: 16036

Date: 7/7/17

Project Name:
USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS

Project Address:
4290 COLUMBIAN ROAD WAMEGO, KS

Sheet Title:

DETAILS


Sheet:
A501

OF:

ROOM FINISH SCHEDULE

ROOM NUMBER	ROOM NAME	FLOOR	BASE	NORTH		EAST		SOUTH		WEST		CEILING		HEIGHT
				MATERIAL	FINISH	MATERIAL	FINISH	MATERIAL	FINISH	MATERIAL	FINISH	MATERIAL	FINISH	
100	CONCESSIONS	SC	R	GYP/CMU	EP	CMU	EP	CMU	EP	GYP/CMU	EP	GYP	9'-6"	
101	WOMENS	SC	R	GYP	EP	GYP	EP	GYP	EP	GYP	EP	GYP	9'-6"	
102	FAMILY	SC	R	GYP	EP	CMU	EP	GYP	EP	GYP	EP	GYP	9'-6"	
103	MENS	SC	R	GYP	EP	GYP	EP	GYP	EP	GYP	EP	GYP	9'-6"	
104	LOCKERS	SC	R	GYP	EP	GYP	EP	CMU	P	GYP	P	GYP	9'-6"	
105	OFFICE	CPT	R	GYP	P	GYP	P	GYP	P	GYP	P	GYP	9'-6"	
106	LOCKERS	CPT	R	GYP	EP	GYP	EP	GYP	EP	GYP	EP	GYP	9'-6"	
107	RESTROOM	ER	EB	GYP	EP	GYP	EP	GYP	EP	GYP	EP	GYP	9'-6"	
108	TRAINING	CPT	R	CMU	P	GYP	P	GYP	P	GYP	P	GYP	9'-6"	
109	LAUNDRY AND STORAGE	SC	R	CMU	P	GYP	P	GYP	P	GYP	P	GYP	9'-6"	
110	ENTRY	ER	EB	CMU	EP	GYP	EP	---	---	GYP	EP	GYP	9'-6"	
111	RESTROOM	ER	EB	CMU	EP	GYP	EP	---	---	GYP/CMU	P	GYP	9'-6"	
112	SHOWER	ER	EB	CMU	EP	CMU	EP	CMU	EP	CMU	EP	GYP	9'-6"	
113	CUSTODIAL	SC	R	GYP	EP	GYP	EP	GYP	EP	GYP	EP	GYP	9'-6"	
114	ENTRY	ER	EB	GYP	EP	GYP	EP	CMU	EP	GYP	EP	APC-2	0'-0"	
115	TEAM MEETING	CPT	R	GYP/CMU	EP	GYP/CMU	EP	GYP	EP	GYP	EP	APC-2	0'-0"	
116	MECHANICAL	SC	R	CMU	P	GYP	P	GYP	P	CMU	P	GYP	9'-6"	
117	VESTIBULE	ER	EB	GYP	EP	GYP	EP	CMU	EP	GYP	EP	GYP	9'-6"	
118	LOCKERS	SC	R	CMU	EP	GYP	EP	CMU	EP	GYP	EP	GYP	9'-6"	
119	RESTROOM	ER	EB	---	---	GYP	EP	GYP	EP	CMU	EP	GYP	9'-6"	
120	SHOWER	ER	EB	CMU	EP	CMU	EP	---	---	CMU	EP	GYP	9'-6"	
121	OFFICE	CPT	R	GYP	P	GYP	P	GYP	P	CMU	P	GYP	9'-6"	
122	RESTROOM	ER	EB	GYP	EP	GYP	EP	CMU	EP	GYP	EP	GYP	9'-6"	
123	OFFICIALS	CPT	R	GYP	P	GYP	P	CMU	P	CMU	P	GYP	9'-6"	

NOTES	
4.15	CARPET TILE
4.16	EPOXY RESIN FLOORING
4.18	SEALED CONCRETE
4.20	POWDER COATED STEEL CORNER GUARD- 2" X 2" ANGLE
10.10	FIRE EXTINGUISHER CABINET
10.13	MARKER BOARD
10.22	ATHLETIC LOCKERS
10.23	TWO TIER LOCKERS



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 - FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

MATERIAL/FINISH KEY

FLOOR FINISHES:
SC - SEALED CONCRETE
CPT - CARPET (SEE FLOOR FINISH PLAN)
ER - EPOXY RESIN

BASE FINISHES:
R - 4" RUBBER BASE- STRAIGHT AT CARPET TILE, COVERED AT HARD FLOORS
EB - EPOXY RESIN BASE

WALL MATERIAL:
CMU - CONCRETE MASONRY UNIT
GYP - GYPSUM WALLBOARD

WALL FINISH:
EP - EPOXY PAINT
P - PAINT


CEILING FINISH:
GYP - GYPSUM BOARD CEILING
APC-2 - ACOUSTIC PANEL CEILING- ARMSTRONG CIRRUS 504

FINISH NOTES:

1. ALL PAINTED OR EPOXY PAINTED WALLS TO MATCH SHERWIN WILLIAMS SW6541 GRECIAN IVORY UNLESS INDICATED ON THE FLOOR FINISH PLAN AS EPOXY PAINT/PAIN 2, WHICH IS TO MATCH SHERWIN WILLIAMS SW6566 HEARTHROB.



2. ALL PAINTED GYPSUM BOARD CEILINGS TO MATCH SHERWIN WILLIAMS SW0004 SNOWBOUND.

3. ALL GYPSUM BOARD WALLS WITHIN 8'-0" OF THE FLOOR TO BE IMPACT RESISTANT TYPE GYPSUM BOARD WITH MOLD RESISTANCE, TYPE X. ALL OTHER GYPSUM BOARD WALLS, SOFFITS AND CEILINGS TO BE TYPE X, EXCEPT MOLD RESISTANT TYPE X IN NET WALL CONDITIONS.



34" TALL PLAM COUNTER SUPPORTED BY 2" X 2" ANGLE WITH 20" LEGS
POWDERCOATED STEEL BRACKETS AT 4'-0" O.C., ANCHOR TO BLOCKING IN WALL.

STAINLESS STEEL COUNTER- ELEVATION AT SAME AS COILING COUNTER SILL, SUPPORTED BY 2" X 2" ANGLE WITH 20" LEGS
POWDERCOATED STEEL BRACKETS AT 4'-0" O.C.



A

B

C

REV	DESCRIPTION	DATE



Project Number: **16036**

Date: **7/7/17**

Project Name:
USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS


Project Address:
4290 COLUMBIAN ROAD WAMEGO, KS

Sheet Title:


ROOM FINISH SCHEDULE

Sheet: **A601**


OF




A5 EXTERIOR HEAD - THICK
A701 3" = 1'-0"




A4 EXTERIOR DOOR DETAIL - HEAD (THIN)
A701 3" = 1'-0"




A3 TYPICAL DOOR HEAD
A701 3" = 1'-0"




C5 EXTERIOR DOOR JAMB
A701 3" = 1'-0"




C4 EXTERIOR DOOR DETAIL - JAMB (THIN)
A701 3" = 1'-0"




C3 TYPICAL DOOR JAMB
A701 3" = 1'-0"



D5 TYPICAL DOOR SILL
A701 3" = 1'-0"




D4 DOOR TYPE 2 - JAMB
A701 3" = 1'-0"



D3 DOOR TYPE 4 - HEAD
A701 3" = 1'-0"

NOTES	
3.1	CONCRETE- SLAB ON GRADE- SEE STRUCTURAL DRWG.
4.1	8" C.M.U.
4.2	8" C.M.U. BOND BEAM
4.5	MASONRY TIE
4.6	SOLID GROUT
4.8	THRU-WALL FLASHING WITH DRIP EDGE
4.9	MORTAR
4.10	4" BURNISHED BLOCK VENEER
4.12	CAVITY DRAINAGE MATERIAL
5.4	STEEL REINFORCING
5.14	STEEL COLUMN- SEE STRUCTURAL DRWG.
5.15	STEEL LINTEL- SEE STRUCTURAL
5.19	STEEL PLATE- SEE STRUCTURAL
7.1	JOINT SEALANT
7.2	BACKER ROD AND SEALANT
7.6	2" RIGID WALL INSULATION
T.12	TERMINATION BAR
T.16	ACOUSTIC BATT INSULATION
T.22	E.I.F.S. VENEER
8.1	ALUMINUM STOREFRONT
8.2	ALUMINUM STOREFRONT DOOR
8.3	HOLLOW METAL DOOR
8.4	HOLLOW METAL FRAME
8.6	GLASS TYPE 1- CLEAR INSUL. TEMPERED
8.15	THRESHOLD
8.16	OVERHEAD COILING DOOR- MOTORIZED
4.1	5/8" TYPE 'X' GYP. BD. IMPACT RESISTANT
4.6	6" METAL STUDS



BBN

BBN ARCHITECTS INC
228 POYNTEZ AVENUE
MANHATTAN, KANSAS 66502
PH: 785-776-4912 FAX: 785-776-0944
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

REV	DESCRIPTION	DATE

Project Number: 16036

Date: 7/7/17


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
WAMEGO, KS**


Sheet Title:
**DOOR AND
WINDOW
DETAIL**

Sheet:
A701


OF:



A4
A102 WINDOW JAMB DETAIL - MASONRY VENEER
 3" = 1'-0"




A3
A102 STEEL COLUMN TO WINDOW DETAIL
 3" = 1'-0"



A2
A102 MASONRY VENEER TO EIFS DETAIL
 3" = 1'-0"


NOTES	
4.1	8" C.M.U.
4.5	MASONRY TIE
4.6	SOLID GROUT
4.9	MORTAR
4.10	4" BURNISHED BLOCK VENEER
5.4	STEEL REINFORCING
5.6	STEEL ANGLE- SEE STRUCTURAL DRWG.
5.7	STEEL TUBE- SEE STRUCTURAL
5.13	STEEL MISC. CHANNEL- SEE STRUCTURAL DRWG.
5.14	STEEL COLUMN- SEE STRUCTURAL DRWG.
5.19	STEEL PLATE- SEE STRUCTURAL
6.8	WOOD BLOCKING
7.1	JOINT SEALANT
7.2	BACKER ROD AND SEALANT
7.6	2" RIGID WALL INSULATION
7.9	METAL SOFFIT DECK- VENTED
7.13	VAPOR BARRIER
7.14	SPANDREL INSULATION
7.15	CELLULOSE INSULATION
7.16	ACOUSTIC BATT INSULATION
7.21	5" X 5" DOWNSPOUT
7.22	E.I.F.S. VENEER
8.1	ALUMINUM STOREFRONT
8.4	HOLLOW METAL FRAME
8.5	ALUMINUM BRAKE METAL
8.6	GLASS TYPE 1- CLEAR INSUL. TEMPERED
8.9	GLASS TYPE 4- CLEAR INSUL. TEMPERED SPANDREL GLASS
8.10	GLASS TYPE 6- CLEAR
8.14	ALUMINUM STOREFRONT DEFLECTION RECEPTOR
9.1	5/8" TYPE 'X' GYP. BD. IMPACT RESISTANT
9.5	3-5/8" METAL STUDS
9.7	TYPE 1 ACOUSTICAL CEILING TILE




BBN

BBN ARCHITECTS INC
 228 POYNTZ AVENUE
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912 - FAX: 785-776-0944
 WWW.BBNARCHITECTS.COM


Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.




C5 Detail *Q*
A102 3" = 1'-0"



C4
A102 WINDOW HEAD - STOREFRONT OFFICE
 3" = 1'-0"



C3
A102 WINDOW JAMB - STOREFRONT OFFICE
 3" = 1'-0"



C2
A102 WINDOW SILL - STOREFRONT OFFICE
 3" = 1'-0"

A

B

C

REV	DESCRIPTION	DATE



Project Number: **16036**

Date: **7/7/17**

Project Name:
**USD 320 SPORTS
 COMPLEX LOCKER
 AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
 WAMEGO, KS**


Sheet Title:

**WINDOW
 DETAILS**

Sheet:
A702

OF:

NOTES	
3.3	EXTERIOR CONCRETE PAVEMENT- SEE CIVIL DRWS.
3.4	CAST-IN-PLACE CONCRETE
3.10	CONCRETE REVEAL- 1"
5.20	ALUMINUM FENCE
1.24	EXPANSION JOINT- PAVEMENT
1.30	EXPANSION JOINT- WALL



BBN


BBN ARCHITECTS INC
 228 POYNTZ AVENUE
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912 - FAX: 785-776-0944
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.


A

B

C



D3 Detail 4
 A103 1/2" = 1'-0"



D2 Detail 3
 A103 1/2" = 1'-0"

REV	DESCRIPTION	DATE

Project Number: **16036**

Date: **7/7/17**


Project Name:
**USD 320 SPORTS
 COMPLEX LOCKER
 AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
 WAMEGO, KS**

Sheet Title:
SITE DETAILS


Sheet:
A703

OF:



NORTH

 FLOOR PLAN- FURNISHINGS
 1/8" = 1'-0"



BBN

BBN ARCHITECTS INC
 228 POYNITZ AVENUE
 MANHATTAN, KANSAS 66502
 PH: 785-776-4912 - FAX: 785-776-0944
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.

REV	DESCRIPTION	DATE
-----	-------------	------



Project Number: **16036**

Date: **7/7/17**

Project Name:
**USD 320 SPORTS
 COMPLEX LOCKER
 AND CONCESSIONS**

Project Address:
**4290 COLUMBIAN ROAD
 WAMEGO, KS**

Sheet Title:
**FURNISHING
 PLAN**

Sheet:
A901


OF:

MECHANICAL SYMBOLS LEGEND


	Thermostat
	90° Elbow down, round duct
	90° Elbow up, round duct
	Round duct offset
	Radius elbow
	90° Elbow down, rectangular supply duct
	90° Elbow up, rectangular supply duct
	90° Elbow down, rectangular return duct
	90° Elbow up, rectangular return duct
	Rectangular elbow with turning vanes
	Flexible duct
	Manual balancing damper
	Motorized damper
	Fire damper
	Smoke damper
	Combination fire/smoke damper
	Ceiling supply air diffuser
	Ceiling return air grille
	Sidewall supply air diffuser
	Sidewall return air grille
	Supply air slot diffuser
	Round tap in bottom of duct
	Rectangular tap in bottom of duct
	Condensate drain
	Cold water
	Hot water
	Tempered water
	Recirculated water
	Recirculated tempered water
	Natural gas
	Sanitary waste above grade
	Sanitary waste below grade
	Sanitary vent
	Vent through roof
	Plumbing trap
	Pipe turning down
	Pipe turning up
	Shock arrester
	Ball valve
	Gas cock
	Union
	Temperature/pressure relief valve
	Strainer
	Aquastat
	Thermometer in well
	Temperature sensor in well
	Connection of new to existing
	Existing device
	Typical
	A.F.F. Above finished floor
	U.N.O. Unless noted otherwise
	N.I.C. Not in contract
	G.C. General Contractor

ELECTRICAL SYMBOLS LEGEND

	Duplex receptacle
	Ground fault interrupting duplex receptacle
	Countertop duplex receptacle
	Weatherproof duplex receptacle
	Four-plex receptacle
	Special receptacle as noted
	Data box
	Countertop data box
	Flush junction box
	Surface or concealed junction box
	Electrical connection to equipment
	Single pole switch
	Three-way switch
	Four-way switch
	Manual motor starter
	Relay switch
	Electrical disconnect switch
	Motor starter
	Electrical motor
	Conduit concealed in wall or ceiling
	In-floor conduit
	Homerun to panelboard with conductors as indicated. Do not share neutrals unless noted otherwise.
	Panelboard
	Transformer
	Electrical meter
	Fire alarm horn/strobe
	Fire alarm pull station
	Fire alarm duct smoke detector
	Fire alarm test switch
	Fire alarm relay/addressable control module
	Fire alarm addressable monitor module
	Fire alarm strobe
	Fire alarm control panel
	Existing device
	C.B. Circuit breaker
	U.N.O. Unless noted otherwise
	A.F.F. Above finished floor
	N.I.C. Not in contract
	TYP. Typical
	G.C. General Contractor



MEP SITE PLAN
1" = 10'-0"



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KS 66502
PH: 785-776-4912
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

REVISIONS:	

Project Number: **16036**

Date: **7/7/17**


Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 Columbian Road
Wamego, KS**

Sheet Title:
**MEP SITE
PLAN**

Sheet:
ME101

Page: **12**



BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KS 66502
PH: 785-776-4912
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.


Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.


Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.



SEQUENCE OF OPERATION:

- Interlock all exhaust fans and RTU-1 such that based on either a time of day occupancy schedule, or manual override activation of a light switch in any restroom, manual override from switch in mechanical 116 or locker room space, all (3) exhaust fans shall start and RTU-1 fan shall start and heating shall modulate based on the sequence below. Coordinate programming of manual override switch and occupancy schedule with E.C.
- Heating:
 - RTU-1 shall modulate gas heating to maintain a setpoint of 70F (adj.) based on base on the average space temperature value returned from (6) temperature sensors. Override control from lighting control panel with signal from line voltage thermostat set to 50°F (adj.) for emergency heating operation.
- Alarms: All room temperature outside of user defined limits, fan failure, deviation of any temperature from setpoint for an adjustable time span, filter dirty.

A RTU-1 EXHAUST FAN INTERLOCK & OVERRIDE DIAGRAM
NOT TO SCALE



GENERAL NOTES

- Coordinate main ductwork routes with roof trusses and route between truss webs.
- Coordinate branch duct run-outs with roof truss locations and route between trusses.

FLOOR PLAN - MECHANICAL
1/8" = 1'-0"

ELECTRIC HEATER SCHEDULE		
Mark	EH-1	EH-2,3,4
Type	Unit Heater	Cove Heater
Airflow	Horizontal Blow	Radiant
Watts	3,300	1,250
Voltage	277	240
Phase	1	1
BASED ON: (Raywall)	HTH5103N	CV125X
Notes:	1. Provide unit with wall mounting bracket. 2. Provide unit with accessories needed for wall mounted thermostat. 3. Provide unit with 240V line voltage thermostat rated for load.	

EXHAUST FAN SCHEDULE			
DESIGNATION	EF-1	EF-2	EF-3
DUTY	EXHAUST	EXHAUST	EXHAUST
AREA SERVED	SEE PLANS	SEE PLANS	SEE PLANS
TYPE	SIDEWALL	SIDEWALL	SIDEWALL
TYPE	CENTRIFUGAL	CENTRIFUGAL	CENTRIFUGAL
CFM	900	1,190	620
EXT. S.P.(WG)	0.50	0.50	0.50
TYPE DRIVE	DIRECT	DIRECT	DIRECT
DESIGN HP OR (WATTS)	1/4	1/4	1/4
MOTOR RPM	1,579	1,671	1,303
MAX. SONES	9.9	11.3	6.9
ACCESSORIES	1,2,3	1,2,3	1,2,3
VOLTAGE/PHASE	120/1	120/1	120/1
BASED ON: (GREENHECK)	CW-099-A	CW-101-A	CW-099-A
ACCESSORY KEY:	1. Provide with backdraft damper. 2. Provide with factory mounted and wired disconnect. 3. Provide unit mounted solid state speed control.		

AIR DEVICE SCHEDULE				
All devices shall be supplied in white finish suitable for field painting.				
SD-A	EH Price AMD/6/4A aluminum louvered flush face diffuser, 24" square face, round neck, gasketed beveled frame. Blow pattern is 4-way unless indicated otherwise.	CFM Range	Max. APD	Max. NC
		0-110	0.10	30
		111-200	0.10	30
		201-300	0.10	30
		301-400	0.10	30
		401-535	0.10	30
	Unless noted otherwise, runouts to diffusers shall be same size as neck.	Neck Dia.		
		6"		
		8"		
		10"		
		12"		
		14"		
SD-B	EH Price AMD/3P/4A aluminum louvered flush face diffuser, 24" square face, round neck, to lay into T-bar ceiling. Blow pattern is 4-way unless indicated otherwise.	CFM Range	Max. APD	Max. NC
		0-110	0.10	30
		111-200	0.10	30
		201-300	0.10	30
		301-400	0.10	30
		401-535	0.10	30
	Unless noted otherwise, runouts to diffusers shall be same size as neck.	Neck Dia.		
		6"		
		8"		
		10"		
		12"		
		14"		
RG-A	EH Price AMD/3P aluminum louvered flush face return grille with 12" square neck, 24" square face, gasketed beveled frame. Neck size as indicated on drawings.			
RG-B	EH Price AMD/3P aluminum louvered flush face return grille with 12" square neck, 24" square face, to lay into T-bar ceiling. Neck size as indicated on drawings.			
EG-A	EH Price 630/L extruded aluminum louvered exhaust air grille with 1-1/4" screwed border and gasketed frame. Size as indicated on drawings.			

ROOF TOP UNIT SCHEDULE			
ROOF TOP UNIT	RTU-1	RTU-2	RTU-3
TYPE	HEATING	HEATING/COOLING	HEATING/COOLING
SERVES	NORTH	TEAM MEETING	OFFICES
CONFIGURATION	DOWNFLOW	HORIZONTAL DISCHARGE	HORIZONTAL DISCHARGE
CFM	3,000	1,400	1,100
EXT. S.P.(WG)	0.75	0.75	0.75
MINIMUM O.A. CFM	3,000	650	380
HEATING FUEL	NATURAL GAS	NATURAL GAS	NATURAL GAS
MAXIMUM HEATING INPUT (MBH)	390	140	100
MINIMUM HEATING OUTPUT (MBH)	315.9	113.4	81
HEATING STAGES	MODULATING	1	1
REFRIGERANT	-	R-410A	R-410A
EVAP. E.A.T. DB(WB (F)	-	87.0/68.49	83.98/66.91
CONDENSER E.A.T. DB(F)	-	105	105
NET SENSIBLE COOLING CAPACITY (MBH)	-	43.75	33.96
NET TOTAL COOLING CAPACITY (MBH)	-	55.65	44.23
SUPPLY AIR FAN RPM (or speed)	1,170	1,589	1,650
SUPPLY FAN HP	2	1	1
SUPPLY FAN DRIVE TYPE	DIRECT	DIRECT	DIRECT
CONDENSER FAN HP	-	0.333	0.333
NO. COMPRESSORS	-	1	1
COMPRESSOR FLA (EACH)	-	25.6	21
TOTAL COOLING F.L.A.	14	40	31
MINIMUM CIRCUIT AMPS	17	47	36
MAXIMUM HACR CIRCUIT BRKR. AMPS	25	70	50
FILTERS	2" DISPOSABLE	2" DISPOSABLE	2" DISPOSABLE
VOLTAGE/PHASE	240/1	240/1	240/1
MINIMUM EER (SEER)	12.4	13.3	13.3
APPROXIMATE WEIGHT INCLUDING CURB, & ACCESSORIES (LBS)	1,300	1,200	1,150
BASED ON: (AAON)	RN-013-3-0-0000-369	RQ-005-1-H-EA09-359	RQ-004-1-H-EA09-339
NOTES:	1. Provide each RTU with a flexible connection at supply and return duct connections and transition as required to duct size. 2. Provide RTU-2 and RTU-3 with modulating hot gas reheat for dehumidification. 3. Provide each RTU with factory installed and wired NEMA 3R disconnect switch. 4. Provide each RTU with factory installed and wired weatherproof GFI NEMA 5-15 receptacle. 5. Provide RTU-1 with 7-day programmable combination thermostat and humidistat. 6. Equip each unit with complete integral control system for thermostat. 7. Install supply air duct smoke detector, provided by Electrical Contractor, in RTU's over 2,000 cfm of supply air. Detector shall be circuited to shut down unit entirely upon detection of smoke. 8. Provide RTU-2 and RTU-3 with 14" high insulated curb compatible with pad mounting on grade. 9. Provide RTU-1 with curb compatible with pad mounting on grade and for horizontal discharge of ductwork from unit through curb. 10. Provide RTU-2 and RTU-3 with factory provided and field installed hail guards. 11. Provide RTU-1 & RTU-3 averaging temperature sensors. Quantities shown on drawings.		

REVISIONS:

1	
2	
3	
4	
5	

THOMAS C. O'RAZEM
PROFESSIONAL ENGINEER
KANSAS
11371
07/07/2017






Project Number: **16036**
Date: **7/7/17**
Project Name: **USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS**
Project Address: **4290 Columbian Road Wamego, KS**

Sheet Title: **MECHANICAL PLAN**
Sheet: **M101**
Job No. 15011-1
Copyright © Orazem & Scalora Engineering, P.A. 2017

ELECTRICAL EQUIPMENT SCHEDULE				
TRANSFORMERS				
Mark	KVA	Mounting	Secondary Conductors	GEC
T1	100	Floor	3#500,#3G	#1/0
Dry type transformer for indoor installation, U.L. listed, compliant with IEEE, NEMA and ANSI standards, single phase, 60 hertz, 480 volt primary 240/120 volt secondary, (6) 2-1/2% full capacity taps, 150 degree C temperature rise, ventilated enclosure and internal vibration isolation core mounting. Provide NEC compliant signage for transformers served by remote disconnects.				
ENCLOSED CIRCUIT BREAKERS				
Mark	Voltage	Poles	Ampacity	Enclosure
CB-L	480	2	300	NEMA 1
Enclosed circuit breaker shall have dual rated cable lugs and be equipped with a neutral terminal and grounding lug. Minimum AIC of 25,000 for 240 volts and 18,000 for 480 volts. Equivalent to Square D LAL.				

BRANCH CIRCUIT PANELBOARD SCHEDULE							
PANEL DESIGNATION: PANEL 'L'		MIN A.I.C.: 10,000		FEATURES:			
LOCATION: Mech 116		MCB Amps: 400		- Panelboard Construction			
VOLTS: 120/240		BUS Amps: 400		- Equipment Ground Bus			
CONFIGURATION: 1 Phase/3 Wire		ENCL.: NEMA 1		- Equal to Square D NQ			
MOUNTING: Surface							
CKT.	Description	Conductors	C/B	CKT.	Description	Conductors	C/B
1	Rcpt - Rooms 118, 119	2#12,#12G	20/1	2	Rcpt - Training 108 West	2#12,#12G	20/1
3	Rcpt - Office 121	2#12,#12G	20/1	4	Rcpt - Ice Machine	2#12,#12G	20/1
5	Rcpt - Electric Water Cooler	2#12,#12G	20/1	6	Rcpt - Refrigerator	2#12,#12G	20/1
7	Rcpt - Locker 118	2#12,#12G	20/1	8	Rcpt - Training 108 East	2#12,#12G	20/1
9	Rcpt - Locker 118	2#12,#12G	20/1	10	Rcpt - Washer	2#12,#12G	20/1
11	Rcpt - Officials 123	2#12,#12G	20/1	12	Rcpt - Dryer	2#12,#12G	30
13	Rcpt - Restroom 122	2#12,#12G	20/1	14			2
15	Rcpt - Team Meeting 115 West	2#12,#12G	20/1	16	Rcpt - Laundry, Storage 109	2#12,#12G	20/1
17	Rcpt - Team Meeting 115 East	2#12,#12G	20/1	18	Rcpt - Womens 101	2#12,#12G	20/1
19	Rcpt - Mechanical 116 West	2#12,#12G	20/1	20	Rcpt - Rooms 102, 103	2#12,#12G	20/1
21	Rcpt - Mechanical 116 East	2#12,#12G	20/1	22	Rcpt - Concessions 100 NWC	2#12,#12G	20/1
23	Rcpt - Rooms 106, 107	2#12,#12G	20/1	24	Rcpt - Concessions 100 NWC	2#12,#12G	20/1
25	Rcpt - Office 105	2#12,#12G	20/1	26	Rcpt - Concessions 100 NWC	2#12,#12G	20/1
27	*Rcpt - Electric Water Cooler	2#12,#12G	20/1	28	Rcpt - Concessions 100 NEC	2#12,#12G	20/1
29	Rcpt - Restroom 111 South	2#12,#12G	20/1	30	Rcpt - Concessions 100 NEC	2#12,#12G	20/1
31	Rcpt - Restroom 111 North	2#12,#12G	20/1	32	Rcpt - Concessions 100 NEC	2#12,#12G	20/1
33	Rcpt - Mechanical 116 North	2#12,#12G	20/1	34	Rcpt - Concessions 100 SEC	2#12,#12G	20/1
35	Rcpt - Rooms 104, 113	2#12,#12G	20/1	36	Rcpt - Concessions 100 E Wall	2#12,#12G	20/1
37	Rcpt - Projector Room 115	2#12,#12G	20/1	38	Rcpt - Concessions 100 SWC	2#12,#12G	20/1
39	EF-1	2#12,#12G	15/1	40	Rcpt - Concessions 100 W Wall	2#12,#12G	20/1
41	EF-2	2#12,#12G	15/1	42	Rcpt - South Exterior	2#12,#12G	20/1
43	EF-3	2#12,#12G	15/1	44	RTU-2	2#8,#10G	45
45	HVAC Controls	2#12,#12G	20/1	46			2
47	RTU-1	2#10,#10G	25	48	RTU-3	2#6,#10G	60
49			2	50			2
51	EH-2, EH-3, EH-4	2#12,#12G	20	52	Existing Panel F	3#6,#10G	60
53			2	54			2
55	EH-1	2#12,#12G	20	56	Ltg - Mech 116	2#12,#12G	20/1
57			2	58	Ltg - West Interior	2#12,#12G	20/1
59	Spare	---	20/1	60	Ltg - East Interior	2#12,#12G	20/1
61	Spare	---	20/1	62	Ltg - Concessions	2#12,#12G	20/1
63	Spare	---	20/1	64	Ltg - Exterior Facade	2#12,#12G	20/1
65	Spare	---	20/1	66	Spare	---	20/1
67	Spare	---	20/1	68	Spare	---	20/1
69	Spare	---	20/1	70	Spare	---	20/1
71	Spare	---	20/1	72	Spare	---	20/1

NOTES:
 * = Provide GFCI protected circuit breaker




BBN ARCHITECTS INC
 228 POYNTZ AVENUE
 MANHATTAN, KS 66502
 PH: 785-776-4912
 WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
 © BBN Architects, Inc.

REVISIONS:


1	
2	
3	
4	
5	




Project Number: 16036
 Date: 7/7/17
 Project Name:
USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS
 Project Address:
4290 Columbian Road Wamego, KS

Sheet Title:
ELECTRICAL DETAILS

Sheet:
E201
 OF: 8




UNDER FLOOR PLUMBING PLAN
1/8" = 1'-0"



PLUMBING FLOOR PLAN
1/8" = 1'-0"

- NOTES BY SYMBOLS**
- 1 2" WASTE FROM FIXTURE OR FLOOR DRAIN ABOVE.
 - 2 4" WASTE UP TO FIXTURE(S) ABOVE.
 - 3 2" VENT UP.
 - 4 2" VENT FROM FLOOR DRAIN OR FIXTURE(S) BELOW.
 - 5 4" WASTE UP TO FWCO.
 - 6 3/4" HW AND 3/4" CW UP IN WALL TO FIXTURES ABOVE.
 - 7 3/4" CW UP IN WALL TO FIXTURE ABOVE.
 - 8 1" HW AND 1" CW UP IN WALL TO FIXTURES ABOVE.
 - 9 3/4" HW AND 2-1/2" CW UP IN WALL TO FIXTURES ABOVE.
 - 10 3/4" HW AND 2" CW UP IN WALL TO FIXTURES ABOVE.
 - 11 1" HW AND 2" CW UP IN WALL TO FIXTURES ABOVE.
 - 12 1-1/4" HW AND 1-1/4" CW UP IN WALL TO FIXTURES ABOVE.
 - 13 2" HOT WATER UP.
 - 14 1-1/4" HW AND 2-1/2" CW UP IN WALL TO FIXTURES ABOVE.
 - 15 3" WASTE FROM FIXTURE ABOVE.
 - 16 PROVIDE MANUFACTURER PROVIDED CONCENTRIC VENT FOR WATER HEATERS. ROUTE COMBUSTION INTAKE AND EXHAUST PIPING THROUGH ATTIC TO ROOF DIRECTLY ABOVE WATER HEATER. INSTALL ALL CONCENTRIC VENTS LEVEL AND EQUALLY SPACED, TYPICAL FOR (4).
 - 17 3/4" HOT WATER AND 3/4" COLD WATER FROM BELOW TO FIXTURE(S).



BBN

BBN ARCHITECTS INC.
228 POYNTZ AVENUE
MANHATTAN, KS 66502
PH: 785-776-4912
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

REVISIONS:

Project Number: **16036**

Date: **7/7/17**

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 Columbian Road
Wamego, KS**

Sheet Title:
**PLUMBING
PLANS**


Sheet:
P101

OF: **8**

ose ORAZEM & SCALORA ENGINEERING, P.A.
Manhattan, Kansas
Job No. 15011-1
Copyright © Orazem & Scalora Engineering, P.A. 2017


PLUMBING FIXTURE MINIMUM ROUGH-IN SIZE SCHEDULE				
FIXTURE/DESIGNATION	WASTE	VENT	COLD WTR.	HOT WTR.
FLUSH VALVE WATER CLOSET/WC-A,B	4"	2"	1"	---
URINAL/UR-A,B	2"	2"	3/4"	---
LAVATORY/LAV-A,B	2"	2"	1/2"	1/2"
SHOWER/SH-A,B,C	2"	2"	1/2"	1/2"
SERVICE SINK/SS-A	3"	2"	1/2"	1/2"
ELECTRIC WATER COOLER/EWC-A	2"	2"	1/2"	---
DRINK FOUNTAIN/DF-A	2"	2"	1/2"	---
CLOTHESWASHER CONNECTION BOX/CCB	2"	2"	1/2"	1/2"
ICE MAKER BOX/IMB	---	---	1/2"	---
WALL HYDRANT/WH-A,B	---	---	3/4"	---
HOSE BIBB/HB-A	---	---	3/4"	---
FLOOR DRAIN/FD-A,B,C,D	2"	2"	---	---

PLUMBING EQUIPMENT SCHEDULE		
General Notes: 1. For fixtures marked (ADA), fixture, trim, mounting dimensions and installation shall meet the requirements of the 2010 Americans With Disabilities Act. 2. Coordinate fixture locations with Architectural plans and elevations prior to rough-in. 3. All fixtures shall be provided with vandal resistant trim. 4. Provide carrier required for complete installation of fixture.		
WC-A	Zurn Z5615 vitreous china, wall mounted, elongated bowl, siphon jet flushing action, 1.6 GPF, 1-1/2" spud toilet, open front seat less cover, Zurn Z6000AV-WS1 flush valve with vacuum breaker and angle stop, coated cast iron closet carrier with adjustable closet connection and with feet anchor bolted to floor. Fixture color: White. Mount with rim at 15 inches AFF.	
WC-B (ADA)	Zurn Z5615 ADA vitreous china, wall mounted, elongated bowl, siphon jet flushing action, 1.6 GPF, 1-1/2" top spud toilet, open front seat less cover, Zurn Z6000AV-WS1 flush valve with vacuum breaker, angle stop and ADA compliant handle, coated cast iron closet carrier with adjustable closet connection and with feet anchor bolted to floor. Fixture color: White. Mount with rim at 17" AFF.	
UR-A	Zurn Z5755-U vitreous china, wall hung washout flushing action, extended rim, 1.0 GPF, 3/4" top spud, integral trap, wall hanger carrier with feet anchor bolted to floor, Zurn Z6003AV-WS1 flush valve with vacuum breaker and angle stop. Fixture color: White. Mount with lip at 24" AFF.	
UR-B (ADA)	Zurn Z5755-U vitreous china, wall hung, washout flushing action, extended rim, 1.0 GPF, 3/4" top spud, integral trap, wall hanger carrier with feet anchor bolted to floor, Zurn Z6003AV-WS1 flush valve with vacuum breaker, ADA compliant handle and angle stop. Fixture color: White. Mount with lip at maximum of 17" AFF.	
LAV-A	Zurn Z5124 self-rimming round vitreous china lavatory, 19" outside diameter, front overflow. Trim with Zurn Z81101-XL-3M 4" centerset faucet with 4" spout, 0.5 gpm flow control, grid drain, indexed hot or cold 2-1/2" metal lever handles, Dearborn supplies with stops and escutcheon plate, Dearborn #760W 17 ga. offset tailpiece and 1-1/4" cast brass P-trap with cleanout plug. Fixture color: White. Insulate water and waste piping below sink with manufactured piping covers consisting of flexible vinyl insulation with white finish and access to piping, equivalent to Handi Lav-Guard manufactured by Truebro Inc.	
LAV-B (ADA)	Zurn Z5344 20" x 18" vitreous china front overflow lavatory for concealed arms. Trim with Zurn Z81101-XL-3M 4" centerset faucet with 4" spout, 0.5 gpm flow control, grid drain, indexes hot or cold 2-1/2" metal lever handles, Dearborn supplies with stops and escutcheon plate, Dearborn #760W 17 ga. offset tailpiece and 1-1/4" cast brass P-trap with cleanout plug. Fixture color: White. Insulate water and waste piping below sink with manufactured piping covers consisting of flexible vinyl insulation with white finish and access to piping, equivalent to Handi Lav-Guard manufactured by Truebro Inc. Provide carrier with feet anchor bolted to floor.	
SH-A	Trim for showers: Zurn Z7301-SS-MT-I2 pressure balancing valve with integral stops, metal lever handle, institutional fixed spray shower head with integral 2.5 GPM flow control. Piping shall be concealed in wall. Install valve at 48" AFF, head at 72" AFF.	
SH-B (ADA)	Provide trim for handicapped accessible shower: Zurn Z7301-SS-MT-DV2P-HW-VB anti-scaud pressure balancing mixing valve with ADA compliant handle, adjustable stop screw to limit handle turn, and integral service stops, Z7000-I2-1.75 institutional fixed spray shower head with integral 1.75 GPM flow control, wall and hand spray unit with 60" of flexible rubber line metal hose with in-line vacuum breaker, wall spout, 24" slide bar with bracket, and diverter valve with ADA compliant metal lever handle. Piping shall be concealed in wall. See Handicapped Accessible Shower Detail for mounting heights.	
SH-C (ADA)	Comfort Designs XST 3838 BF RRF 1.0 RRF-1 36" x 36" x 78-7/8" ADA compliant gelcoat shower enclosure, center sloping floor, center drain location with self caulking brass shower drain, curtain rod, ADA compliant 1-1/2" dia. stainless steel grab bars, 1" threshold. Color: White. Trim with Zurn Z7300-SS-MT-VB anti-scaud pressure balancing mixing valve with ADA compliant handle, adjustable stop screw to limit handle turn, and integral service stops, hand spray unit with 60" of flexible rubber lined metal hose with in-line vacuum breaker, wall spout, 24" slide bar with bracket. Piping shall be concealed in wall. See Handicapped Accessible Shower Detail for mounting heights. Enclosure shall be recessed in floor to maintain ADA compliant threshold.	
EWC-A (ADA)	Halsey Taylor #HTHB-HACGB two-level, lead free, wall hung electric drinking fountain with front mounted push bars for water control, single water chilling unit with capacity to cool 8.0 GPH from 80 degrees F to 50 degrees F at 90 degrees F room temperature, with Refrigerant 134a, and single plumbing and electrical rough-in. Tops shall be stainless steel, frame shall be heavy duty welded steel with beige steel cabinet. Provide with supply stops and 1-1/4" Dearborn 17 gauge cast brass P-trap with cleanout plug. Electrical characteristics: 120 volt/1 phase, 4.8 F.L.A. Provide with bottle filling station with 1.1 GPM fill rate.	
DF-A (ADA)	Halsey Taylor #HDFB-BLEBP two-level, lead free stainless steel drinking fountain with freeze resistant boxes to be installed inside the building, vandal-resistant bubblers, self-closing vandal-resistant actuation mechanism, 1-1/4" 17 gauge P-traps with cleanout plug, mounting carrier. See Architectural Elevations for mounting height.	
CCB	Guy Gray B200 clotheswasher connection box, recessed housing with 1/2" valved hot and cold water top or bottom supply connections as required, and knockout for 2" drain connection. Galvanized steel construction.	
IMB	Guy Gray BIM875AB icemaker connection box, 20 gauge galvanized steel faceplate, 20 gauge galvanized steel recessed housing with 1/2" lead free valved cold water supply connection.	
WH-A	Wade W-8600 non-freeze wall hydrant, cast bronze with satin bronze face, 3/4" inlet and brass casing of sufficient length to extend through walls as required to place valve inside building. Valve rod and seat washer shall be removable through the face of the hydrant. Hydrant shall be furnished complete with detachable T-handle and integral vacuum breaker.	
HB-A	Woodford model 26, hose bibb, cast bronze, with rough chrome finish, wheel handle, 3/4" inlet and hose thread outlet. Hose bibb shall be furnished complete with no spray back integral vacuum breaker.	
FD-A	Floor drain for finished areas - Wade 1100-1 floor drain with clamping collar, adjustable, vandal proof, 6" satin nickel bronze top. Provide with ProSet Systems trap guard T25630-F.	
FD-B	Floor drain for mechanical rooms - Wade Z350-27 cast iron with bottom outlet, 8" square top, square loose set grate, and removable sediment bucket. Provide with ProSet Systems trap guard T25630-F.	
FD-C	Floor drain for showers - Zurn ZS880-28 4" x 28" stainless steel shower drain with bottom outlet, adjustable top with Type 304 stainless steel slotted heel-proof grate. Fabricated stainless steel body with V shaped channel, 2" No-Hub center drain, secured leveling frame. Provide with ProSet Systems trap guard T25630-F.	
FD-D	Floor drain Sioux Chief 841-2P 2" PVC floor drain with 6" dia polypropylene strainer.	
FWCO	Wade 8560-E cleanout tee with brass threaded plug and 8480-R round stainless steel coverplate secured to plug by countersunk screw.	
FGCO	Finished grade cleanout, Wade 6000-2 cast iron cleanout with straight body and fitted with pressure countersunk plug, same size as soil pipe with ductile iron scoriated cover. Bring extra heavy cast iron riser pipe to grade. Terminate hub flush in center of 18"x18"x4" (18" x 36" x 4" for two way cleanout) concrete block when not located in concrete area.	
FFCO	Finished floor cleanout, Wade 6000-Z-1 cast iron finished floor cleanout with spigot outlet, threaded adjustable housing, flanged ferrule with bronze threaded plug and vandal proof round secured nickel bronze scoriated top.	
HWH-A	A.O. Smith BTH-199 gas fired direct vent water heater, 100gallon storage, 199 MBH natural gas input, 261 gallon per hour recovery at 90 degrees F rise.	
MXV-A	Leonard #TM-520B-LF-DT-IT high-low thermostatic water mixing valve assembly for exposed exposed piping with Type TM Thermostatic Water Mixing Valve with solid bimetal thermostat directly linked to valve porting, adjustable limit stops, color coded scale, wall support, inlet union angle strainer checkstops, outlet volume control/shutoff, pressure regulating valve with pressure gauges, Type TM Thermostatic Water Mixing Valve with solid bimetal thermostat directly linked to valve porting, assembly shall be capable of providing 29 gpm of tempered water at 10 psi pressure drop, 1.0 gpm minimum flow rate, adjustable limit stops, color coded scale, outlet volume control/shutoff, dial thermometer (range: 0 degrees F to 140 degrees F), rough bronze finish.	
HWP-A	Hot water circulation pump, Taco #005-BF, in-line, 4GPM @ 9 ft. head, 1/35 HP, bronze body, 3250 RPM, 120 volt, 1 phase, 3/4" flanges. Provide bronze companion flanges and aquasat control.	
SA-A	Wade Shock Arrestors, stainless steel construction with welded nested bellows, precharged with nitrogen, 125 psi maximum operating pressure, 300 degree F maximum temperature. Fixture Units Designation Wade Catalog No. PDI Rating 1-11 SA-5 5 A 12-32 SA-10 10 B 33-60 SA-20 20 C	
TEA-A	Thermal Expansion Absorber, Amtral ST-85CL precharged hydropneumatic steel expansion tank with replaceable internal butyl bladder. 22.0 gallons total volume, 11.0 gal minimum expansion volume, bottom system connection, 150 psig maximum working pressure.	
SS-A	Flat MSB2424 24"x24"x10" deep Molded Stone one piece service sink with drain and strainer. Trim with Zurn Z843M1-XL-CS faucet with top brace, service stops, check stops, indexed 2-1/2" hot and cold metal lever handles, bucket hook, vacuum breaker, and threaded hose end spout, polished chrome plated finish. Fixture color: White.	



BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KS 66502
PH: 785-776-4912
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unaltered work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.



B HOT WATER HEATER DETAIL
NOT TO SCALE


REVISIONS:

THOMAS C. O'RAZEM
LICENSED PROFESSIONAL ENGINEER
KANSAS
11371
07/07/2017


Project Number: 16036
Date: 7/7/17
Project Name: USD 320 SPORTS COMPLEX LOCKER AND CONCESSIONS
Project Address: 4290 Columbian Road Wamego, KS

Sheet Title: PLUMBING DETAILS


Sheet: P201
OF 8




A VALVE PIT PIPING DETAIL
NOT TO SCALE




B WATER PIPING DIAGRAM
RESTROOM 107
NOT TO SCALE




C WATER PIPING DIAGRAM
RESTROOM 119
NOT TO SCALE




D WATER PIPING DIAGRAM
RESTROOM 111
NOT TO SCALE




E WATER PIPING DIAGRAM
RESTROOM 122
NOT TO SCALE




F WATER PIPING DIAGRAM
RESTROOM 111 AND SHOWER 112
NOT TO SCALE




G WATER PIPING DIAGRAM
SHOWER 112
NOT TO SCALE




H WATER PIPING DIAGRAM
WOMENS 101, MENS 103, FAMILY 102
NOT TO SCALE



I WATER PIPING DIAGRAM
WOMENS 101
NOT TO SCALE



J WATER PIPING DIAGRAM
MENS 103
NOT TO SCALE




BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KS 66502
PH: 785-776-4912
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

REVISIONS:	
△	
△	
△	
△	
△	
△	




Project Number: 16036
Date: 7/7/17

Project Name:
**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**


Project Address:
**4290 Columbian Road
Wamego, KS**

Sheet Title:
**PLUMBING
DETAILS**


Sheet:
P202
01




A WASTE RISER DIAGRAMS
RESTROOM 103
NOT TO SCALE




B WASTE RISER DIAGRAMS
MENS 103 & WOMENS 101
NOT TO SCALE




C WASTE RISER DIAGRAMS
RESTROOM 122
NOT TO SCALE




D WASTE RISER DIAGRAMS
RESTROOM 119 & LOCKER 118
NOT TO SCALE




E WASTE RISER DIAGRAMS
SHOWER 120
NOT TO SCALE




F WASTE RISER DIAGRAMS
RESTROOM 111
NOT TO SCALE




G WASTE RISER DIAGRAMS
WOMENS 101
NOT TO SCALE



H WASTE RISER DIAGRAMS
SHOWER 112 & RESTROOM 111
NOT TO SCALE



I WASTE RISER DIAGRAMS
SHOWER 112
NOT TO SCALE




BBN

BBN ARCHITECTS INC
228 POYNTZ AVENUE
MANHATTAN, KS 66502
PH: 785-776-4912
WWW.BBNARCHITECTS.COM

Information provided on the drawings regarding existing conditions has been obtained from the best sources available, but cannot be guaranteed in all respects. Contractor shall verify all such information prior to proceeding with any new work that may be affected. Include as part of the contract all work required to produce the indicated result. All drawings and written material appearing herein constitute the original and unpublished work of the Architect, and same may not be duplicated, used or disclosed without the written consent of the Architect.
© BBN Architects, Inc.

REVISIONS:	
△	
△	
△	
△	
△	



Project Number: 16036

Date: 7/7/17

Project Name:

**USD 320 SPORTS
COMPLEX LOCKER
AND CONCESSIONS**

Project Address:
**4290 Columbian Road
Wamego, KS**

Sheet Title:

**PLUMBING
DETAILS**

Sheet:

P203

OF 8